



400 Chisholm Place, Suite 418  
Plano, Texas 75075

Telephone: (469)241-0950 Telecopier: (469)241-0956

## MATERIAL SAFETY DATA SHEET

### EMERGENCY OVERVIEW

This milky, slippery liquid has health hazards upon exposure to vapors generated at high temperatures, may cause respiratory irritation. Harmful, possible risk of irreversible effects if swallowed. May cause irritation to eyes and skin. Get immediate medical attention if ingested.

**NFPA RATING: HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 0**

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**GENERIC NAME:** Hydraulic fluid

**ISSUE DATE:** February 21, 2006

**THIS LUBRICANTS USA PRODUCT IS:**

**FRW FLUID**

**CAS NUMBER:**

Mixture

**SYNONYMS / GENERAL NAMES:**

Fire resistant hydraulic fluid (invert emulsion)

**24 HOUR EMERGENCY TELEPHONE:**

(CHEMTREC) 1-800-424-9300

**TECHNICAL INFORMATION:**

1-800-442-5823

### 2. COMPOSITION / INFORMATION ON INGREDIENTS / HAZARDOUS INGREDIENTS

| COMPONENTS                               | CAS NO.    | %      | HAZARD DATA   |
|--|------------|--------|---|
| Petroleum, hydrotreated heavy paraffinic | 64742-54-7 | 50-70  | For finished fluid mists  |
| Water                                    | 7732-18-5  | 37-43% | ACGIH TW 5 mg/m <sup>3</sup> (mist)                                     |
| Proprietary ingredients                  | NA         | 0-10   | STEL 10 mg/m <sup>3</sup> (mist)<br>OSHA TWA 5 mg/m <sup>3</sup> (mist) |

### 3. HAZARDOUS IDENTIFICATION

|                                |  |
|--------------------------------|--|
| <b>ROUTES OF ENTRY:</b>        | Skin contact, inhalation, ingestion.   |
| <b>TARGET ORGANS:</b>          | Skin, lungs, eyes, kidneys, liver  |
| <b>INHALATION:</b>             | Spray mist can irritate airways and lungs. Heating can generate vapors that may cause respiratory irritation, nausea and headaches.<br><br>Inhalation hazard at room temperature is unlikely due to the low volatility of this product. Single exposure to vapors is not likely to be hazardous. |
| <b>IRRITANCY:</b>              | This product can cause mild, transient, eye irritation with short-term contact with liquids or sprays. This material can cause mild skin irritation from prolonged or repeated skin contact. Injection of petroleum hydrocarbons requires immediate medical attention.                           |
| <b>REPRODUCTIVE EFFECTS:</b>   | No available information.  |
| <b>CANCER INFORMATION:</b>     | IARC-not listed. OSHA--not regulated. NTP-not listed   |
| <b>CHRONIC HEALTH EFFECTS:</b> | Unknown  |

### 4. FIRST AID MEASURES

|              |   |
|--------------|---|
| <b>EYES:</b> | May cause moderate corneal injury. Check for and remove contact lenses. Flush eyes with cool, clean, low-pressure water while occasionally lifting and lowering eyelids. Seek medical |
|--------------|---|

|                    |   |
|--------------------|---|
|                    | attention.  |
| <b>DERMAL:</b>     | A single prolonged exposure is not likely to result in the material being absorbed through skin in harmful amounts. Remove contaminated shoes and clothing, wipe off excess material. Wash exposed skin with soap and water. Seek medical attention if tissue appears damaged or if irritation. Thoroughly clean contaminated clothing before reuse. Discard contaminated leather goods.  |
| <b>INGESTION:</b>  | DO NOT INDUCE VOMITING. Administer large amounts of water. Never give anything by mouth to an unconscious person. Seek medical attention immediately.   |
| <b>INHALATION:</b> | Vapors are minimal under ambient conditions due to physical properties: If overcome by vapor of hot product, immediately remove from source of exposure. Get medical attention if any discomfort continues. If victim is not breathing, immediately begin rescue breathing. If breathing is difficult, a qualified individual should administer 100 percent humidified oxygen. Seek medical attention immediately. Keep the affected individual warm and at rest. |
| <b>INJECTION:</b>  | Injection of fluid requires immediate medical attention.  |

#### 5. FIRE FIGHTING MEASURES

|  |  |
|--|--|
| <b>FLASH POINT, °C (°F):</b>           | N/D (burns only after water is evaporated off)   |
| <b>FLAMMABLE LIMITS (% BY VOLUME):</b> | <b>LOWER:</b> N/D <b>UPPER:</b> N/D  |
| <b>EXTINGUISHING MEDIA:</b>            | Use dry chemical, alcohol resistant foam, carbon dioxide or water fog.   |
| <b>SPECIAL PROPERTIES:</b>             | This is a non-flammable, aqueous solution. After the water component evaporates, the remaining material will burn. |
| <b>AUTOIGNITION TEMPERATURE:</b>       | N/A  |
| <b>EXPLOSION DATA:</b>                 | N/A  |
| <b>NFPA RATING:</b>                    | <b>HEALTH:</b> <u>1</u> <b>FLAMMABILITY:</b> <u>0</u> <b>REACTIVITY</b> <u>0</u>                                   |
| <b>INSTRUCTIONS:</b>                   | Pressure will increase in over heated, closed containers.  |

#### 6. ACCIDENTAL RELEASE MEASURES

|                           |  |
|---------------------------|--|
| <b>SPILL PROCEDURES:</b>  | Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Slipping hazard—avoid walking through spilled material. Stop leak if you can do so without risk. For small spills, absorb or cover with dry earth, sand, or other inert non-combustible absorbent material and place into waste containers for later disposal. Contain large spills to maximize product recovery or disposal. Prevent entry into waterways or sewers. In urban area, cleanup spills as soon as possible. In natural environments, seek cleanup advice from specialists to minimize physical habitat damage. Absorbent pads and similar materials can be used. Comply with all laws and regulations. |
| <b>Ecotoxicity</b>        | Discharges are expected to cause only localized and non-persistent environmental damage. Expected to be toxic to many water organisms. Not expected to bioconcentrate in aquatic organisms. Fish are threatened because of lack of oxygen  |
| <b>Environmental fate</b> | The product will contaminate water. Biodegradation in soil and water is a major fate process. For detailed ecological call the non-emergency number shown in section 1.  |

#### 7. HANDLING AND STORAGE

|   |  |
|---|--|
| <b>HANDLING &amp; STORAGE PROCEDURES:</b> | Avoid skin and eye contact. Keep lid closed when not in use. Do not reuse container. Ventilate well. Avoid water contamination and extreme temperatures to minimize product degradation. Do not store with strong oxidizing agents. Do not store at temperatures above 120°F or in direct sunlight for extended periods of time.   |
|   | Empty containers may contain product residues that can ignite with explosive force. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to flames, sparks, heat or other potential ignition sources. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers and/or waste residues of this product. |

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

|   |  |
|---|--|
| <b>ENGINEERING CONTROLS:</b>            | Provide exhaust ventilation or other engineering controls to keep the airborne concentration of mists and/or vapors below the recommended exposure limits. An eye wash station and safety shower should be located near the workstation.   |
| <b>GLOVES PROTECTION:</b>               | Use gloves constructed of chemical resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. Use heat protective gloves when handling product at elevated temperatures.   |
| <b>EYE PROTECTION:</b>                  | Safety glasses equipped with side shields should be adequate protection under most conditions of use. Wear goggles and/or face shield if splashing or spraying is likely, especially if material is heated above 125° F (or 51° C). Have suitable eye wash water available.  |
| <b>RESPIRATORY PROTECTION:</b>          | Vaporization or misting is not expected at ambient temperatures. Therefore, the need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist prefilter should be used. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134). |
| <b>CLOTHING RECOMMENDATION:</b>         | Avoid prolonged and/or repeated skin contact. If splashing or spraying is expected chemical-resistant (Tyvek®, nitrile or neoprene) clothing should be worn. This might include long-sleeves, apron, slicker suit, boots and additional facial protection. If general contact occurs, promptly remove soaked clothing and take a shower.   |
| <b>OTHER COMMENTS:</b>                  | Use good personal hygiene practices. Wash hands and other exposed skin areas with plenty of mild soap and water before eating, drinking, smoking, use of toilet facilities or leaving work. Since standards/control limits have not been established for this product, the exposure limits shown below are suggested as minimum control guidelines.  |
| <b>Occupational exposure guidelines</b> | Applicable workplace exposure levels<br><br>TWA: 20; STEL; NE (mg/M <sup>3</sup> ) from ACGIH (TLV)<br>TWA: 20; STEL; 30 (mg/ M <sup>3</sup> ) from OSHA (PEL)   |

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                      |                               |
|--------------------------------------|-------------------------------|
| <b>APPEARANCE:</b>                   | Milky liquid                  |
| <b>ODOR:</b>                         | Mild petroleum odor           |
| <b>pH:</b>                           | NA                            |
| <b>VAPOR PRESSURE, mm Hg (25°C):</b> | >1                            |
| <b>VAPOR DENSITY:</b>                | >1                            |
| <b>MELTING POINT:</b>                | NA                            |
| <b>BOILING POINT, 760 mm Hg, °C:</b> | >100 C (212 F)                |
| <b>SOLUBILITY IN WATER:</b>          | Soluble in cold water.        |
| <b>SPECIFIC GRAVITY:</b>             | 0.93 (Water = 1). 7.7 lbs/gal |
| <b>EVAPORATION RATE:</b>             | <1 (n-butyl acetate = 1)      |
| <b>VISCOSITY 40°C (100°C)</b>        | 100 cSt @ 40 C                |
| <b>MOLECULAR WEIGHT:</b>             | N/A                           |
| <b>PERCENT VOLATILE:</b>             | Negligible volatility         |

## 10. STABILITY AND REACTIVITY

|                               |  |
|-------------------------------|--|
| <b>STABILITY:</b>             | Stable   |
| <b>INCOMPATIBILITY:</b>       | Strong oxidizers   |
| <b>POLYMERIZATION:</b>        | Will not occur   |
| <b>THERMAL DECOMPOSITION:</b> | Oxides of nitrogen and carbon such as CO <sub>2</sub> , CO, smoke, fumes, aldehydes, ketones, organic acids and polymer fragments. |

## 11. TOXICOLOGICAL INFORMATION

|                           |   |
|---------------------------|---|
| <b>OVERVIEW</b>           | No experimental toxicological data on the preparation as such is available.                   |
| <b>DERMAL IRRITATION:</b> | Product is mildly irritating to the skin and slightly toxic on prolonged or repeated contact. |

|   |    |
|---|----|
| <b>TOXICITY:</b>                          | ND |
| <b>INGESTION IRRITATION:</b>              | ND |
| <b>AGGRAVATED MEDICAL CONDITIONS:</b>     | ND |
| <b>CHRONIC OR ACUTE EXPOSURE SYMPTOMS</b> | ND |
| <b>OTHER REMARKS</b>                      | ND |

## 12. HEALTH INFORMATION

**HMIS CODE:**      **HEALTH:**    1    **FIRE:**      1    **REACTIVITY:**    0

|    |                     |    |                             |
|----|---------------------|----|-----------------------------|
| No | <b>HIGHLY TOXIC</b> | No | <b>SENSITIZER</b>           |
| No | <b>TOXIC</b>        | No | <b>REPRODUCTIVE EFFECTS</b> |
| No | <b>CORROSIVE</b>    | No | <b>MUTAGEN</b>              |
| No | <b>IRRITANT</b>     |    |                             |

## 13. DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL:**      It is the responsibility of the user to determine if the material is a hazardous waste at the time of disposal. Determine compliance status with all applicable requirements prior to disposal.

## 14. TRANSPORT INFORMATION

### DOT (DEPARTMENT OF TRANSPORTATION)

|                                      |                              |
|--------------------------------------|------------------------------|
| <b>PROPER SHIPPING NAME:</b>         | N/A                          |
| <b>HAZARD CLASS:</b>                 | Not a DOT regulated material |
| <b>HAZARD IDENTIFICATION NUMBER:</b> | N/A                          |
| <b>DOT PLACARD:</b>                  | N/A                          |
| <b>COMPATIBILITY CATEGORY:</b>       | N/A                          |

## 15. REGULATORY INFORMATION

### **SARA SECTION 313 - TOXIC CHEMICALS:**

This product contains no toxic chemicals under SARA Section 313 and 40 CFR Part 372.

### **SARA SECTION 311 - HAZARD CATEGORIES:**

This product may meet one or more of the criteria for the hazard categories defined in 40 CFR Part 370 as established by Sections 311 and 312 of SARA as indicated below:

|    |  |    |  |
|----|--|----|--|
| NO | <b>IMMEDIATE (ACUTE) HEALTH HAZARD</b> | NO | <b>SUDDEN RELEASE OF PRESSURE HAZARD</b> |
| NO | <b>DELAYED (CHRONIC) HEALTH HAZARD</b> | NO | <b>REACTIVE HAZARD</b>                   |
| NO | <b>FIRE HAZARD</b>                     |    |  |

### **SARA SECTION 302 – EXTREMELY HAZARDOUS WASTE:**

This product is not known to contain any components in concentrations greater than one percent that are listed as Extremely Hazardous Substances in 40 CFR Part 355 pursuant to the requirements of Section 302(a) of SARA.

### **CLEAN WATER ACT (CWA):**

Under the CWA, discharges of fluids to surface water without proper Federal and State permits must be reported immediately to the National Response Center at (800) 424-8802. Discharges or spills which produce a visible sheen on waters of the US, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's national response center at 800-424-8802

### **CERCLA HAZARDOUS SUBSTANCES:**

As defined by CERCLA, the term "hazardous substance" includes any ingredients or fraction thereof, which is not otherwise specifically listed or designated as a hazardous substance. Chemical substances present in

this product that may be subject to this statute are: NONE

### **U.S. TSCA INVENTORY**

This product and or its components are listed on the TSCA inventory.

### **CALIFORNIA PROPOSITION 65**

This product contains trace amounts of ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute. Cadmium <1 ppm, Arsenic < 1 ppm, lead < 1 ppm.

### **NEW JERSEY RIGHT-TO-KNOW LABEL**

Invert emulsion hydraulic fluid.

### **ADDITIONAL REGULATORY REMARKS**

N/D

## **16. OTHER INFORMATION**

The information in this Material Safety Data Sheet should be provided to all who will use, handle, store, transport, or otherwise be exposed to this product. This information was prepared for the guidance of plant engineering, operations and management and for persons working with or handling this product. Lubricants USA believes this information to be reliable and up to date as of the date of publication, but makes no warranty that it is.

|                           |           |            |              |          |             |
|---------------------------|-----------|------------|--------------|----------|-------------|
| <b>NFPA HAZARD RATING</b> | least - 0 | slight - 1 | moderate - 2 | high - 3 | extreme - 4 |
| <b>HMIS HEALTH RATING</b> | least - 0 | slight - 1 | moderate - 2 | high - 3 | extreme - 4 |

AP = approximately    EQ = equal    > = greater than    < = less than    NA = not applicable  
 ND = no data    NE = not established

ACGIH = American Conference of Governmental Industrial Hygienists  
 AIHA = American Industrial Hygiene Association  
 CERCLA = Comprehensive Environmental Response, Compensation and Liability Act (1980)  
 EPA = Environmental Protection Agency  
 HMIS = Hazardous Materials Information System  
 IARC = International Agency for Research on Cancer  
 NFPA = National Fire Protection Association  
 NIOSH = National Institute of Occupational Safety and Health  
 NLGI = National Lubricating Grease Institute  
 NPCA = National Paint and Coating Manufacturers Association  
 NTP = National Toxicology Program  
 OSHA = Occupational Safety and Health Administration  
 RQ = Reportable quantity  
 SARA = Superfund Amendments and Reauthorization Act (1986)  
 TSCA = Toxic Substance Control Act