



400 Chisholm Place, Suite 418
Plano, Texas 75075

Telephone: (469)241-0950 Telecopier: (469)241-0956

MATERIAL SAFETY DATA SHEET

EMERGENCY OVERVIEW

This slippery liquid has a mild odor. No significant immediate hazards for emergency response are known.

NFPA RATING: HEALTH: 0 FLAMMABILITY: 1 REACTIVITY: 0

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

GENERIC NAME: LUBRICATING OIL

ISSUE DATE:

February 23, 2009

THIS LUBRICANTS USA PRODUCT IS:

RAILROAD JOURNAL OIL

CAS NUMBER:

Mixture

SYNONYMS / GENERAL NAMES:

Industrial oil

24 HOUR EMERGENCY TELEPHONE:

(CHEMTREC) 1-800-424-9300

TECHNICAL INFORMATION:

1-800-442-5823

2. COMPOSITION / INFORMATION ON INGREDIENTS / HAZARDOUS INGREDIENTS

COMPONENTS	CAS NO.	%	HAZARD DATA
1) Highly-refined paraffinic petroleum oils	64741-88-4 or 64741-89-5	0-90	*
2) Hydrotreated naphthenic petroleum oils	64742-53-6 or 64742-52-5	0-70	*
3) Proprietary ingredients	Mixture	0-3	
4) Barium compounds	61790-48-5	0-1	
5) Calcium sulfonate	Proprietary	0-1	

* Not limited to but include these CAS numbers. Hazard data on this petroleum oil is Oral LD 50 >5000, Dermal LD 50 >2000

HAZARDOUS INGREDIENTS:

NONE

HAZARDOUS PER 29 CFR 1916.1200:

NO

3. HAZARDOUS IDENTIFICATION

ROUTES OF ENTRY:	Skin contact
TARGET ORGANS:	Skin
IRRITANCY:	This product can cause mild, transient, eye irritation with short-term contact with liquids or sprays.
INJECTION SENSITATION:	Injection under the skin, in muscle, or into the blood stream can cause irritation, inflammation, swelling, fever, and systemic effects and mild central nervous system depression. Injection of pressurized hydrocarbons can cause severe, permanent tissue damage. Initial symptoms may be minor. Injection of petroleum hydrocarbons requires immediate medical attention.
INGESTION	Laxative effect in smaller doses. Large volume can cause headache, drowsiness, nausea, vomiting and diarrhea.
CHRONIC EXPOSURE SYMPTOMS	Prolonged or repeated contact is toxic to lungs, digestive system, skin and eyes.
REPRODUCTIVE EFFECTS:	N/A

Product Code(s)

Source Codes c

CANCER INFORMATION:	This product does not contain any components at concentrations above 0.1% that are considered carcinogenic by OSHA, IARC, or NTP.
----------------------------	---

4. FIRST AID MEASURES

EYES:	Check for and remove contact lenses. Flush eyes with cool, clean, low-pressure water while occasionally lifting and lowering eyelids. Seek medical attention if excessive tearing, redness or pain persists.
DERMAL:	Remove contaminated shoes and clothing, wipe off excess material. Wash exposed skin with soap and water. Seek medical attention if tissue appears damaged or if irritation persists. Thoroughly clean contaminated clothing before reuse. Discard contaminated leather goods.
INGESTION:	Do not induce vomiting unless directed to by a physician. Do not give anything to drink unless directed to by a physician. Never give anything by mouth to a person who is not fully conscious. Seek medical attention immediately.
INHALATION:	Move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If breathing is difficult, a qualified individual should administer 100 percent humidified oxygen. Seek medical attention immediately. Keep the affected individual warm and at rest.
INJECTION:	Injection of pressurized hydrocarbons can cause severe, permanent tissue damage. Initial symptoms may be minor. Injection of petroleum hydrocarbons requires immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASH POINT, °C (°F):	>176°C (367°F)
FLAMMABLE LIMITS (% BY VOLUME):	LOWER: NO DATA UPPER: NO DATA
EXTINGUISHING MEDIA:	Use dry chemical, foam, carbon dioxide or water fog.
SPECIAL FIRE FIGHTING PROCEDURES:	N/A
AUTOIGNITION TEMPERATURE:	N/A
EXPLOSION DATA:	N/A
NFPA RATING:	HEALTH: <u> 0 </u> FLAMMABILITY: <u> 1 </u> REACTIVITY <u> 0 </u>

6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:	Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Slipping hazard—do not walk through spilled material. Stop leak if you can do so without risk. For small spills, absorb or cover with dry earth, sand, or other inert non-combustible absorbent material and place into waste containers for later disposal. Contain large spills to maximize product recovery or disposal. Prevent entry into waterways or sewers. In urban area, cleanup spills as soon as possible. In natural environments, seek cleanup advice from specialists to minimize physical habitat damage. This material will float on water. Absorbent pads and similar materials can be used. Comply with all laws and regulations.
--------------------------	---

7. HANDLING AND STORAGE

HANDLING & STORAGE PROCEDURES:	Avoid water contamination and extreme temperatures to minimize product degradation. Keep container closed. Do not store with strong oxidizing agents. Do not store at temperatures above 120°F or in direct sunlight for extended periods of time. Empty containers may contain product residues that can ignite with explosive force. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to flames, sparks, heat or other potential ignition sources. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers and/or waste residues of this product.
---	--

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:	Provide exhaust ventilation or other engineering controls to keep the airborne concentration of mists and/or vapors below the recommended exposure limits. An eye wash station and safety shower should be located near the workstation.
GLOVES PROTECTION:	Use gloves constructed of chemical resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. Use heat protective gloves when handling product at elevated temperatures.
EYE PROTECTION:	Safety glasses equipped with side shields should be adequate protection under most conditions of use. Wear goggles and/or face shield if splashing or spraying is likely, especially if material is heated above 125° F (or 51° C). Have suitable eye wash water available.
RESPIRATORY PROTECTION:	Vaporization or misting is not expected at ambient temperatures. Therefore, the need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist prefilter should be used. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134).
CLOTHING RECOMMENDATION:	Avoid prolonged and/or repeated skin contact, especially after this product has been used. If splashing or spraying is expected chemical-resistant (Tyvek®, nitrile or neoprene) clothing should be worn. This might include long-sleeves, apron, slicker suit, boots and additional facial protection. If general contact occurs, promptly remove soaked clothing and take a shower.
OTHER COMMENTS:	Use good personal hygiene practices. Wash hands and other exposed skin areas with plenty of mild soap and water before eating, drinking, smoking, use of toilet facilities or leaving work. DO NOT use gasoline, kerosene, solvents or harsh abrasives as skin cleaners. Since standards/control limits have not been established for this product, the exposure limits shown below are suggested as minimum control guidelines.
Occupational exposure guidelines for components	Applicable workplace exposure levels Petroleum lubricant oils TWA: 5 (mg/M ³) STEL 10 (mg/M ³) from ACGIH (TLV) TWA: 5 (mg/ M ³) from OSHA (PEL) Barium compounds TWA 0.5 (mg/M ³) from ACGIH TLV TWA: 0.5 (mg/M ³) from OSHA PEL

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Amber liquid
ODOR:	Mild petroleum odor
pH:	N/A
VAPOR PRESSURE, mm Hg (25°C):	<0.1
VAPOR DENSITY:	>1 (Air =1)
MELTING POINT:	Not available
BOILING POINT, 760 mm Hg, °C:	Not available
SOLUBILITY IN WATER:	Insoluble in cold water.
SPECIFIC GRAVITY:	0.88 (Water = 1)
EVAPORATION RATE:	N/A
VISCOSITY 40°C (100°C)	65 cSt @ 40° C
MOLECULAR WEIGHT:	N/A
PERCENT VOLATILE:	Negligible volatility

10. STABILITY AND REACTIVITY

STABILITY:	Stable
INCOMPATIBILITY:	Strong oxidizers
POLYMERIZATION:	Not expected to occur
THERMAL DECOMPOSITION:	CO ₂ , CO, smoke, fumes, unburned hydrocarbons and trace oxides

	of sulfur, nitrogen.
--	----------------------

11. TOXICOLOGICAL INFORMATION

TOXICITY DATA (components):	<p>Petroleum distillates (paraffinic and naphthenic components)</p> <p>ORAL LD 50 Acute > 5000 mg/kg (rat)</p> <p>DERMAL LD50 Acute >2000 mg/kg (rabbit)</p> <p>Distillates, petroleum, hydrotreated light naphthenic</p> <p>INHALATION LC50 Acute: 9.6 mg/l to 10.5 mg/l (rats)</p> <p>DRAIZE EYE Acute: Non-irritating (rabbit)</p> <p>DRAIZE DERMAL Acute: Mild skin irritant (rabbit)</p> <p>BUEHLER DERMAL Acute: Non-sensitizing (guinea pig)</p> <p>28 DAY DERMAL Sub-Chronic: Mild to moderate skin irritant (rabbit & rat)</p> <p>Petroleum distillates—(paraffinic or naphthenic)—general information</p> <p>Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentration of mineral oil mists, well above applicable workplace exposure levels, include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mists at or near work place exposure levels produced no significant toxicological effects. In long-term studies (up to two years) no carcinogenic effects have been reported in any animal species tested. Analyses conducted by method IP 346 indicate that the polycyclic aromatic concentration is below 3.0 weight percent.</p> <p>A lifetime dermal application of severely hydrotreated light naphthenic oils produced skin masses on mice which correlated with the skin irritation response levels of test animals. Additional studies indicate that light naphthenic oils are not mutagenic, tumor initiators or complete chemical carcinogens.</p>
------------------------------------	--

12. HEALTH INFORMATION

HMIS CODE: HEALTH: 0 FIRE: 1 REACTIVITY: 0

No	HIGHLY TOXIC	No	SENSITIZER
No	TOXIC	No	REPRODUCTIVE EFFECTS
No	CORROSIVE	No	MUTAGEN
No	IRRITANT		

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Recovered non-usable material may be regulated by the US EPA as a hazardous waste (RCRA) due to its barium content (D005). Conditions of use may cause this material to become a "hazardous waste" as defined by federal or state regulations. It is the responsibility of the user to determine if the material is a hazardous waste at the time of disposal. Determine compliance status with all applicable requirements prior to disposal.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME:	Petroleum lubricating oil.
HAZARD CLASS:	Not a DOT controlled material (United States).
HAZARD IDENTIFICATION NUMBER:	N/A
DOT PLACARD:	N/A
COMPATIBILITY CATEGORY:	N/A
OTHER	HAZMAT STCC No. 2911415

15. REGULATORY INFORMATION

SARA SECTION 313 - TOXIC CHEMICALS:

This product does not contain toxic chemicals under SARA Section 313 and 40 CFR Part 372.

SARA SECTION 311 - HAZARD CATEGORIES:

This product may meet one or more of the criteria for the hazard categories defined in 40 CFR Part 370 as established by Sections 311 and 312 of SARA as indicated below:

NO	IMMEDIATE (ACUTE) HEALTH HAZARD	NO	SUDDEN RELEASE OF PRESSURE HAZARD
NO	DELAYED (CHRONIC) HEALTH HAZARD	NO	REACTIVE HAZARD
NO	FIRE HAZARD		

SARA SECTION 302 - EXTREMELY HAZARDOUS WASTE:

This product is not known to contain any components in concentrations greater than one percent that are listed as Extremely Hazardous Substances in 40 CFR Part 355 pursuant to the requirements of Section 302(a) of SARA.

CLEAN WATER ACT (CWA):

Under the CWA, discharges of crude oil and petroleum products to surface water without proper Federal and State permits must be reported immediately to the National Response Center at (800) 424-8802.

CERCLA HAZARDOUS SUBSTANCES:

As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof, which is not otherwise specifically listed or designated as a hazardous substance.

U.S. TSCA INVENTORY

All components of this material are on the U.S. TSCA Inventory or are not required to be listed on the U.S. TSCA Inventory

CALIFORNIA PROPOSITION 65

This product may contain the following components for which the State of California has found to cause cancer, birth defects or other reproductive harm: Toluene <0.02%

NEW JERSEY RIGHT-TO-KNOW LABEL

Petroleum oil.

ADDITIONAL REGULATORY REMARKS

None

16. OTHER INFORMATION

The information in this Material Safety Data Sheet should be provided to all who will use, handle, store, transport, or otherwise be exposed to this product. This information was prepared for the guidance of plant engineering, operations and management and for persons working with or handling this product. Lubricants USA believes this information to be reliable and up to date as of the date of publication, but makes no warranty that it is.

NFPA HAZARD RATING	least - 0	slight - 1	moderate - 2	high - 3	extreme - 4
HMIS HEALTH RATING	least - 0	slight - 1	moderate - 2	high - 3	extreme - 4

AP = approximately EQ = equal > = greater than < = less than NA = not applicable
ND = no data NE = not established

ACGIH = American Conference of Governmental Industrial Hygienists.....AIHA = American Industrial Hygiene Association
CERCLA = Comprehensive Environmental Response, Compensation and Liability Act (1980)
EPA = Environmental Protection Agency.....HMIS = Hazardous Materials Information System
IARC = International Agency for Research on Cancer.....NFPA = National Fire Protection Association
NIOSH = National Institute of Occupational Safety and Health.....NLGI = National Lubricating Grease Institute
NPCA = National Paint and Coating Manufacturers Association.....NTP = National Toxicology Program
OSHA = Occupational Safety and Health Administration.....RQ = Reportable quantity
SARA = Superfund Amendments and Reauthorization Act (1986).....TSCA = Toxic Substance Control Act

Product Code(s)

Source Codes c