



Keystone Lubricants Division
Total Fina Elf Lubricants USA, Inc.
5 N. Stiles Street, Linden NJ 07036

REVISION DATE
06-MAY-98

DATE ISSUED
06-JAN-03

IDENTIFICATION AND EMERGENCY INFORMATION

PRODUCT NAME: SURETAP	PRODUCT #: 200266
CHEMICAL NAME: N/A - Mixture	CAS #'S: Mixture
PRODUCT APPEARANCE AND ODOR: Pale yellow liquid, slight chemical odor	CHEMICAL FAMILY: Polyalkalene glycol
SYNONYMS: Synthetic tapping fluid	EMERGENCY TELEPHONE: 1-908-862-9300

COMPONENTS AND HAZARD INFORMATION

COMPONENTS:	W/W	HAZARD DATA (TLV, LD50, LC50, ETC.):
Water CAS # 7732-18-5		n/e
Polyalkylene glycol mixture CAS # n/a		n/e
Diethanolamine CAS # 111-42-2		TWA 3ppm

For further information see the Toxicity section.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS):

Health	Flammability	Reactivity
1	0	0

TRANSPORTATION INFORMATION

TRANSPORTATION INCIDENT INFORMATION:

DOT: Not regulated.

EMERGENCY FIRST AID

EYE CONTACT:
If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN CONTACT:
In case of skin contact, remove contaminated clothing and wash skin thoroughly with soap and water.

Keystone Lubricants Division
Total Fina Elf Lubricants USA, Inc.
5 N. Stiles Street, Linden NJ 07036

REVISION DATE
06-MAY-98

DATE ISSUED
06-JAN-03

EMERGENCY FIRST AID

INHALATION:

For effects produced by overexposure, remove to fresh air. If effects persist, obtain medical advice.

INGESTION:

If ingested, call a physician immediately. Possible aspiration hazard.

FIRE AND EXPLOSION HAZARD INFORMATION

FLASH POINT (MINIMUM):
N/A

AUTOIGNITION TEMPERATURE:
N/A

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) - HAZARD IDENTIFICATION:

Health	Flammability	Reactivity
1	0	0

FLAMMABLE OR EXPLOSIVE LIMITS (approximate percent by volume in air):
Estimated values: N/A

EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES:

Foam, water spray (fog), dry chemical, carbon dioxide extinguishing agents may all be suitable for extinguishing fires involving this type product, depending on size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists. Wear self contained breathing apparatus and full turn out gear. Cool fire exposed containers with water spray. Dried material can burn.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

n/a

"EMPTY" CONTAINER WARNING:

Empty containers retain residue (liquid or vapor) and can be dangerous. Do NOT pressurize, weld, cut braze, solder, drill, grind or expose such containers to heat, flame, sparks, or other sources of ignition; they may explode and cause injury or death. Do NOT attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged, and returned to a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with government regulations.

HEALTH AND HAZARD INFORMATION

EXPOSURE LIMIT FOR TOTAL PRODUCT: N/E

VARIABILITY AMONG INDIVIDUALS:

Health studies have shown that many petroleum hydrocarbons and synthetic lubricants pose potential human health risks which vary from person to person. As a precaution, exposure to liquids, vapors, mists, or fumes should be minimized.

EFFECTS OF OVEREXPOSURE (Signs and symptoms of exposure):

Prolonged or repeated skin contact with this product tends to remove skin oils

Keystone Lubricants Division
Total Fina Elf Lubricants USA, Inc.
5 N. Stiles Street, Linden NJ 07036

REVISION DATE
06-MAY-98

DATE ISSUED
06-JAN-03

HEALTH AND HAZARD INFORMATION

possibly leading to irritation and dermatitis.
Product contacting the eye may cause irritation.
Possible aspiration hazard. Induced vomiting may cause aspiration of
product into the lungs.
(See Emergency First Aid Section).

PHYSICAL DATA

The following data are approximate or typical values and should not be used
for precise design purposes.

BOILING RANGE:
Wide range

VAPOR PRESSURE:
n/e

SPECIFIC GRAVITY (25°C/25°C):
(WATER = 1)
> 1.0

VAPOR DENSITY (AIR = 1):
n/e

MOLECULAR WEIGHT:
Wide range

PERCENT VOLATILE BY VOLUME:
85 %

EVAPORATION RATE @ 1 ATM. AND 25°C
(77°F) (n-BUTYL ACETATE = 1):
> 1.0

SOLUBILITY IN WATER @ 1 ATM. and 25°C
(77°F):
Soluble

POUR, CONGEALING OR MELTING POINT:
n/e

FREEZING POINT:
n/e

REACTIVITY

This product is stable and will NOT react violently with water. Hazardous
polymerization will not occur. Avoid contact with strong oxidants such as
liquid chlorine, concentrated oxygen, sodium hypochlorite or calcium
hypochlorite.

Do not mix with nitrites due to the possible formation of nitrosamines.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS:

Fumes, smoke, carbon monoxide and other decomposition products, in case of
incomplete combustion.

CONDITIONS TO AVOID:

Open flames.

TOXICITY

Medical Conditions Aggravated by Exposure: Unknown

This product does NOT contain any ingredients identified as carcinogenic by
IARC, NTP, or OSHA.

Keystone Lubricants Division
Total Fina Elf Lubricants USA, Inc.
5 N. Stiles Street, Linden NJ 07036

REVISION DATE
06-MAY-98

DATE ISSUED
06-JAN-03

TOXICITY

SARA Section 313 Status: This product contains the following
Section 313 reportable ingredients:

Component	CAS #	%
Diethanolamine	111-42-2	1.5

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Keep product out of sewers and watercourses by diking or impounding. Absorb with sand or inert material. Sweep or scoop up and remove. Prevent spread of spill. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with local regulations.

WASTE DISPOSAL METHOD: (Consult federal, state, or local authorities for proper disposal procedures.)

Assure conformity with applicable disposal regulations. Dispose of absorbed material at an approved waste site or facility.

PROTECTION AND PRECAUTIONS

VENTILATION: (Always maintain below permissible exposure limits.)
Use local exhaust to capture vapor, mist or fumes, if necessary.

RESPIRATORY PROTECTION: (Use only NIOSH approved equipment.)
Normally not needed at ambient temperatures.

PROTECTIVE GLOVES:

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION:

Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT:

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact.

WORK PRACTICES/ENGINEERING CONTROLS:

Keep containers closed when not in use. Do not handle near heat, sparks, flame, or strong oxidants. DO NOT MIX WITH NITRITES OR PRODUCTS WHICH CONTAIN NITRITES.

PERSONAL HYGIENE:

Minimize breathing vapor, mist, or fumes. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean before reuse. Cleanse skin thoroughly after contact, before breaks and meals, and at end of work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.



MATERIAL SAFETY DATA SHEET
FOR SURETAP

Page 5

Keystone Lubricants Division
Total Fina Elf Lubricants USA, Inc.
5 N. Stiles Street, Linden NJ 07036

REVISION DATE
06-MAY-98

DATE ISSUED
06-JAN-03

PREPARED BY: Luke McHale

REGULATORY MANAGER

THE ABOVE INFORMATION IS ACCURATE TO THE BEST OF OUR KNOWLEDGE.
HOWEVER, SINCE DATA, SAFETY STANDARDS, AND GOVERNMENT REGULATIONS ARE
SUBJECT TO CHANGE AND THE CONDITIONS OF HANDLING AND USE, OR MISUSE
BEYOND OUR CONTROL, SELLER MAKES NO WARRANTY, EITHER EXPRESS OR
IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE
INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE
THEREON. USER SHOULD SATISFY HIMSELF THAT HE HAS ALL CURRENT DATA
RELEVANT TO HIS PARTICULAR USE.