

MATERIAL SAFETY DATA SHEET FOR VESTAN FM #2 GREASE NA

TOTAL Lubricants USA Southwest
400 Chisholm Place, Suite 418
Plano, Texas 75075

TOTAL Lubricants USA, Inc.
5 N. Stiles Street
Linden NJ 07036

REVISION DATE
N/A

DATE ISSUED
3-September-2009

IDENTIFICATION AND EMERGENCY INFORMATION

PRODUCT NAME: VESTAN FM #2 GREASE
PRODUCT #: 1-39774
CHEMICAL NAME: N/A-Mixture
CAS #'S: Mixture
PRODUCT APPEARANCE AND ODOR: White gel, petroleum odor
CHEMICAL FAMILY: Petroleum hydrocarbon
SYNONYMS: Petroleum-based grease
EMERGENCY TELEPHONE: 1-800-442-5823 or 1-908-862-9300

COMPONENTS AND HAZARD INFORMATION

COMPONENTS: W/W HAZARD DATA (TLV, LD50, LC50, ETC.):
White mineral oil 5 mg/m3 TWA (OSHA, ACGIH) as oil mist
CAS# 8042-47-5
Aluminum Complex Soap (proprietary) 10 to 20%
Proprietary ingredients remainder 1 to 10%

* Paraffinic base oil used are not limited to but include these CAS numbers.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS):
Health 1 Flammability 1 Reactivity 0

TRANSPORTATION INFORMATION

TRANSPORTATION/SHIPPING INFORMATION:
Department of Transportation (DOT): Not regulated

EMERGENCY FIRST AID

EYE CONTACT:
If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN CONTACT:
As with all petroleum products, if this product contacts skin, wash affected area thoroughly with soap and water to prevent irritations from occurring. Oil soaked clothing should be removed and laundered frequently to minimize skin contact with product. Prolonged contact with skin may cause irritation.

INHALATION:
Vapor pressure is very low. Vapor inhalation under ambient conditions is normally not a problem. If overcome by vapor from hot product, immediately remove from exposure and call a physician. If breathing is irregular or has stopped, start resuscitation; administer oxygen if available. If overexposure to oil mist, remove from further exposure until excessive oil mist condition subsides.

MATERIAL SAFETY DATA SHEET FOR VESTAN FM #2 GREASE NA

TOTAL Lubricants USA Southwest
400 Chisholm Place, Suite 418
Plano, Texas 75075

TOTAL Lubricants USA, Inc.
5 N. Stiles Street
Linden NJ 07036

REVISION DATE
N/A

DATE ISSUED
3-September-2009

PHYSICAL DATA

The following data are approximate or typical values and should not be used for precise design purposes.

BOILING RANGE:
Wide range

VAPOR PRESSURE:
< 0.1 @ 38°C/100°F

SPECIFIC GRAVITY (25°C/25°C):
(WATER = 1)
< 1.0

VAPOR DENSITY (AIR = 1):
> 8

MOLECULAR WEIGHT:
Wide range

PERCENT VOLATILE BY VOLUME:
Negligible

EVAPORATION RATE @ 1 ATM. AND 25°C
(77°F) (n-BUTYL ACETATE = 1):
< 1.0

SOLUBILITY IN WATER @ 1 ATM. and 25°C
(77°F):
Negligible

POUR, CONGEALING OR MELTING POINT:
n/e

FREEZING POINT:
n/e

REACTIVITY

This product is stable and will NOT react violently with water. Hazardous polymerization will not occur. Avoid contact with strong oxidants such as liquid chlorine, concentrated oxygen, sodium hypochlorite or calcium hypochlorite.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS:

Fumes, smoke, carbon monoxide and other decomposition products, in case of incomplete combustion.

CONDITIONS TO AVOID:

Open flames.

TOXICITY

ORAL (Acute) N/E
DERMAL (Acute) N/E
EYE N/E
INHALATION (Acute) N/E

CHRONIC, SUBCHRONIC, ETC. N/E

Medical Conditions Aggravated by Exposure: Unknown

This product does NOT contain any ingredients identified as carcinogenic by IARC, NTP, or OSHA.

SARA Section 313 Status: This material is not known to contain any chemicals on the SARA Section 313 list at a concentration greater than 1.0 percent or carcinogenic chemical on that list at a concentration greater than 0.1 percent.

MATERIAL SAFETY DATA SHEET FOR VESTAN FM #2 GREASE NA

TOTAL Lubricants USA Southwest
400 Chisholm Place, Suite 418
Plano, Texas 75075

TOTAL Lubricants USA, Inc.
5 N. Stiles Street
Linden NJ 07036

REVISION DATE
N/A

DATE ISSUED
3-September-2009

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Keep product out of sewers and watercourses by diking or impounding. Absorb with sand or inert material. Sweep or scoop up and remove. Prevent spread of spill. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with local regulations.

WASTE DISPOSAL METHOD: (Consult federal, state, or local authorities for proper disposal procedures.) Assure conformity with applicable disposal regulations. Dispose of absorbed material at an approved waste site or facility.

PROTECTION AND PRECAUTIONS

VENTILATION: (Always maintain below permissible exposure limits.)

Use local exhaust to capture vapor, mist or fumes, if necessary. Provide ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. No smoking, or use of flame or other ignition source

RESPIRATORY PROTECTION: (Use only NIOSH approved equipment.)

Normally not needed at ambient temperatures. Use supplied air respiratory protection in confined or enclosed spaces, if needed. Use filter, dust, fume, or mist respirator type under misting conditions. Use can or cartridge; gas or vapor respirator type under conditions exceeding TWA standard.

PROTECTIVE GLOVES:

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION:

Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT:

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact.

WORK PRACTICES/ENGINEERING CONTROLS:

Keep containers closed when not in use. Do not handle near heat, sparks, flame, or strong oxidants.

PERSONAL HYGIENE:

Minimize breathing vapor, mist, or fumes. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean before reuse; discard if oil-soaked. Cleanse skin thoroughly after contact, before breaks and meals, and at end of work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

PREPARED BY: Alan Denniston

VP PRODUCT MANAGEMENT

THE ABOVE INFORMATION IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, SINCE DATA, SAFETY STANDARDS, AND GOVERNMENT REGULATIONS ARE SUBJECT TO CHANGE AND THE CONDITIONS OF HANDLING AND USE, OR MISUSE BEYOND OUR CONTROL, SELLER MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. USER SHOULD SATISFY HIMSELF THAT HE HAS ALL CURRENT DATA RELEVANT TO HIS PARTICULAR USE.