



UNIVERSAL ATF

(Dexron® III-G Quality ATF)

UNIVERSAL ATF is a high quality, automatic transmission fluid that can be used in many types of transmissions. It is an unlicensed product that is suitable for use in General Motors, Ford, Chrysler, American Motors and other transmissions (prior to 2005 model year) that specify DEXRON®-III, DEXRON®-IIE, DEXRON®-II or MERCON® fluid.

In addition to automobile transmissions, it is recommended for use in powershift transmissions that require Allison C-4 or Caterpillar TO-2 fluid. This versatility makes **UNIVERSAL ATF** ideal for mixed fleet application.

UNIVERSAL ATF exhibits excellent oxidation stability, resistance to rust, corrosion, wear and foaming. In addition, the product contains a friction-modifying additive that allows transmissions to shift smoothly while attaining a positive lockup. All of these factors yield an oil that provides a long, trouble-free service life.

The same superior oxidation resistance and wear prevention ability that has proven to protect transmissions serves to protect many rotary air compressors and hydraulic systems. **UNIVERSAL ATF** is an excellent fluid for many such applications; especially where low temperatures are encountered.

TYPICAL CHARACTERISTICS

Product	Universal ATF
Product Code	12101
API Gravity (ASTM D-1298)	32.1
Color	Red
Viscosity (ASTM D-445):	
cSt @ 40°C	33
cSt @ 100°C	7.2
SUS @ 100°F	167
SUS @ 210°F	50
Viscosity Index (ASTM D-2270)	188
Pour Point (ASTM D-97) °F (°C)	-40 (-40)
Flash Point (ASTM D-92) °F (°C)	380 (193)

The above data is subject to usual manufacturing variation. For more information and availability, call 1-800-442-LUBE.
06/23/2005

DEXRON® and **MERCON®** are registered trademarks of General Motors Corporation and Ford Motor Company, respectively.