



ALLISON C-3 FLUID

ALLISON C-3 FLUID is a high quality torque fluid designed specifically for transmissions and torque converters that require an Allison C-3 type fluid.

ALLISON C-3 FLUID is formulated from quality paraffinic base stocks and a high performance additive package. It contains a variety of additives that perform specialized duties. Detergents and dispersants control deposits. Rust and corrosion inhibitors protect metal surfaces. Defoamants prevent air entrainment. Anti-wear agents provide extra wear protection for long component life.

ALLISON C-3 FLUID is recommended for Allison CL(B) T-700 transmissions used in heavy-duty trucks, buses and earth-moving equipment. It is also recommended for many

powershift transmissions, industrial torque converters and any application requiring an Allison C-2 or C-3 fluid.

Use Pontonic DTO 10 for most applications requiring Allison C-4 fluid..

BENEFITS:

- LENGTHENS COMPONENT LIFE WITH EXCELLENT ANTI-WEAR PROTECTION
- GUARDS AGAINST SLUDGE AND VARNISH DEPOSITS
- RESISTS OXIDATION TO MAXIMIZE OIL DRAIN INTERVALS

TYPICAL CHARACTERISTICS

Product Code	14400
API Gravity (ASTM D-1298)	29.5
Viscosity (ASTM D-445):	
cSt @ 40°C	43
cSt @ 100°C	6.5
SUS @ 100°F	225
SUS @ 210°F	48
Viscosity Index (ASTM D-2270)	98
Pour Point (ASTM D-97) °F (°C)	-22 (-30)
Flash Point (ASTM D-92) °F (°C)	420(216)
Color (ASTM D-1500)	2.0

The above data is subject to usual manufacturing variation. For more information and availability, call 1-800-442-LUBE.
7/28/2008