



COMPRESSOR 26087-C OIL

(Naphthenic Compressor Oil)

COMPRESSOR 26087-C is made from high quality naphthenic oil meeting the requirements of MIL PRF 26087-C (grade 2) specification. These oils exhibit good flow characteristics at low temperatures making them suitable for cold weather service.

COMPRESSOR 26087-C is high-quality, additive-type oil recommended for the lubrication of multistage compressor cylinders and special rotary sliding vane compressors in air and inert gas service. It contains no metals and has very low ash.

BENEFITS:

- MIL PRF 26087-C QUALITY
- SOFT CARBON RESIDUE
- GOOD LOW TEMPERATURE FLOW PROPERTIES
- WEAR, RUST AND OXIDATION INHIBITED OIL

TYPICAL CHARACTERISTICS

Product Code	15180
ISO Viscosity Grade	Between 220 & 320
Specific gravity	0.916
Viscosity (ASTM D-445):	
cSt @ 40°C	248
cSt @ 100°C	15.7
cSt @ 100°F	290
cSt @ 210°F	16.2
Viscosity Index (ASTM D-2270)	23
Pour Point (ASTM D-97) °F (°C)	-5 (-21)
Flash Point (ASTM D-92)	
°F	430
(°C)	(221)
Color (ASTM D-1500)	4.0

The above data is subject to usual manufacturing variation. For more information and availability, call 1-800-442-LUBE.
10/09/01