



# PF&F OILS—ISO SERIES

## (Colorless Process Oils)

**PF&F OILS** are colorless highly refined paraffinic mineral oils intended for non-critical general-purpose lubrication such as bearings and gears operating under moderate loads and temperatures, machine tools, and electric motors. They have a high viscosity index and are designed for a wide variety of process applications where low color is important.

### APPLICATIONS:

- Dilution agent for inks and petroleum
- Form release oil
- Process oil in rubber and plastic manufacturing
- General purpose lubricating oil for non-critical applications
- Candle oil

### TYPICAL CHARACTERISTICS

Product Code	-	-	-	17208
Grade	22	46	68	100
API Gravity (ASTM D-1298)	34.1	32.9	31.4	30.3
Viscosity (ASTM D-445):				
cSt @ 40°C	21.	41.1	59	115
cSt @ 100°C	4.2	6.23	7.9	12.2
SUS @ 100°F	109	212	305	600
SUS @ 210°F	40.2	47.1	53	68.5
Viscosity Index (D-2270)	100	97	95	95
Specific Gravity @ 60°F	0.854	0.861	0.868	0.871
Pour Point (ASTM D-97)				
°F	-9	-9	+5	+10
(°C)	(-23)	(-23)	(-15)	(-12)
Flash Point (ASTM D-92)				
°F	390	419	464	500
(°C)	(199)	(215)	(240)	(260)
Color (ASTM D-1500)	0.0	0.0	0.0	0.0
Color (Saybolt)	+25	+24	+23	+22

The above data is subject to usual manufacturing variation. For more information and availability, call 1-800-442-LUBE.  
10/10/2006