



PONTONIC P.M. GEAR OILS

(API GL-1 Pure Mineral Gear Oil)

PONTONIC PURE MINERAL (P. M.) GEAR OILS are straight mineral gear oils that satisfy API Service GL-1 specifications. They are primarily used in truck manual transmissions.

PONTONIC P. M. GEAR OILS are blended from highly refined, paraffinic base oils. This provides good low temperature flowability and high temperature stability.

PONTONIC P. M. GEAR OILS are recommended for many manual transmissions, automotive worm gears and other applications where API GL-1 oil is required. **PONTONIC P. M. GEAR OILS**

are not recommended for hypoid axles and other gears where oils containing extreme pressure additives are specified.

BENEFITS:

- **ECONOMICAL**
- **GOOD LOW TEMPERATURE FLOWABILITY**
- **RESIST SLUDGE AND VARNISH BUILDUP**

TYPICAL CHARACTERISTICS

Product Code	28177	28178
SAE Viscosity Grade	90	140
API Gravity (ASTM D-1298)	28.0	27.4
Viscosity (ASTM D-445)		
cSt @ 40°C	226	480
cSt @ 100°C	19	32
SUS @ 100°F	1200	2580
SUS @ 210°F	97	157
Viscosity Index (ASTM D-2270)	94	97
Pour Point (ASTM D-97) °F (°C)	0 (-18)	5 (-15)
Flash Point (ASTM D-92) °F (°C)	425 (218)	470 (243)
Color (ASTM D-1500)	6.0	6.5

The above data is subject to usual manufacturing variation. For more information and availability, call 1-800-442-LUBE.
7/28/2008