



TECH SPRAY OIL

(Cotton Spindle Oil)

TECH SPRAY OIL is a specially formulated light pale lubricant developed for the cotton industry. **TECH SPRAY OIL** makes the raw cotton fiber easier to handle as well as protect machine parts. In the field, **TECH SPRAY OIL** is a spindle-moistening agent in the picking operation. It prevents balling and eliminates rust and staining. In the gin, **TECH SPRAY OIL** reduces green leaf clinging and dissolves plant juices. This results in a more usable fiber, controls dust and corrosion, and allows ginning immediately after picking. During drawing and spinning operation, **TECH SPRAY OIL** reduces static electricity for a smoother yarn. This makes the fibers more flexible and easier to work.

This is ideal for use as crop duster smoke oil since it keeps the injectors clog free.

BENEFITS:

- LIGHT PALE NONSTAINING LUBRICANT
- PROTECTS MACHING PARTS
- MAKES RAW COTTON FIBER EASIER TO HANDLE
- PREVENTS BALLING
- EMINATES RUST AND STAINING
- DISSOLVES PLANT JUICES
- CONTROLS DUST AND CORROSION
- REDUCES STATIC ELECTRICITY

TYPICAL CHARACTERISTICS

Product Code	17659
API Gravity (ASTM D-1298)	34.5
Viscosity (ASTM D-445):	
cSt @ 40°C	11.0
cSt @ 100°C	2.8
SUS @ 100°F	64
SUS @ 210°F	35
Viscosity Index (ASTM D-2270)	86
Pour Point (ASTM D-97) °F (°C)	0 (-18)
Flash Point (ASTM D-92) °F (°C)	360 (182)
Color (ASTM D-1500)	0.5

The above data is subject to usual manufacturing variation. For more information and availability, call 1-800-442-LUBE.
1/20/2009