



COMPRESSOR OIL SB

(Synthetic Blend Compressor Oil)

COMPRESSOR OIL SB is made from high quality ingredients with low volatility. These oils exhibit good flow characteristics at low temperatures and resist oxidation at high temperature making them suitable for compressor applications.

COMPRESSOR OIL SB is high-quality, additive-type oil recommended for the lubrication of rotary and reciprocating air compressors. It is formulated to reduce deposits and keep parts clean. **COMPRESSOR OIL SB** contains no metals and has very low ash.

BENEFITS:

- RESISTS OXIDATION
- KEEPS VALVES CLEAN
- GOOD LOW TEMPERATURE FLOW PROPERTIES
- WEAR, RUST AND OXIDATION INHIBITED OIL
- HIGH FLASH POINT

TYPICAL CHARACTERISTICS

Product Code	41010	41011	41012	41013	41014
ISO Viscosity Grade	32	46	68	100	150
Color—Amber liquid	Yes	Yes	Yes	Yes	Yes
Specific gravity	0.877	0.877	0.876	0.876	0.879
Viscosity (ASTM D-445):					
cSt @ 40°C	31.2	45.8	66.3	99.2	147
cSt @ 100°C	5.27	6.68	8.48	11.2	14.6
cSt @ 100°F	163	237	346	524	769
cSt @ 210°F	43.9	48.6	54.8	64.7	77.9
Viscosity Index (ASTM D-2270)	99	97	97	99	98
Pour Point (ASTM D-97) °F (°C)	-30 (-34)	-30 (-34)	-25 (-32)	-25 (-32)	-22 (-30)
Flash Point (ASTM D-92)					
°F	420	445	470	520	495
(°C)	(216)	(229)	(243)	(271)	(257)
4-Ball Wear Scar, mm	0.6	0.6	0.6	0.8	0.6

The above data is subject to usual manufacturing variation. For more information and availability, call 1-800-442-LUBE.
11/29/2006