



## **DEXRON® VI ATF** **(Automatic Transmission Fluids)**

**DEXRON®-VI** is a super premium quality, multi-purpose automatic transmission fluid that can be used in many types of transmissions. It is fully approved and licensed for use in General Motors and other transmissions that specify **DEXRON®-VI**, **DEXRON® III** and all earlier generations of **DEXRON®** Automatic transmission fluid. It is also backward compatible and recommended for transmissions calling for Ford **MERCON®** fluid. In addition to automobile transmissions, it may be used in powershift transmissions that require Allison C-4 or Caterpillar TO-2 fluid. This versatility makes **DEXRON®-VI ATF** ideal for mixed fleet application.

**DEXRON®-VI ATF** is blended with highly refined base stocks and selected additives. It exhibits superior oxidation stability as well as excellent resistance to rust, corrosion and foaming. This next generation fluid contains friction-modifying additives that allow transmissions to shift smoothly, yet attain a positive lockup. **DEXRON® VI ATF** is specially formulated to meet the stricter performance requirements for new GM 6-speed automatic transmission.

The same superior oxidation resistance and wear prevention ability that has proven to protect transmissions serves to protect many rotary air compressors and hydraulic systems. **DEXRON®-VI ATF** is an excellent fluid for many such applications; especially where low temperatures are encountered.

**DEXRON®-VI ATF** is also an excellent shear stable multigrade ISO 32 grade hydraulic fluid. It meets Denison Hydraulics HF-0, Vickers (Eaton) M-2950-S and I-286-S.

**Check owner's manual for specific recommendations.**

### **BENEFITS:**

- MULTI-FUNCTIONAL FLUID
- MEETS NEWEST CAR MAKER WARRANTY REQUIREMENTS
- EXCELLENT SHEAR STABILITY & SEAL COMPATIBILITY
- EXTREMELY LONG SERVICE LIFE
- SHIFTS SMOOTHLY WITH POSITIVE LOCKUP

### **APPLICATIONS:**

**DEXRON®-III/MERCON® ATF** is recommended for the following applications:

- All late model GM, American Motors, Chrysler and most imported car, light truck and van automatic transmissions, as well as, those in Ford vehicles that call for Mercon® fluid. It is specifically designed for 6-speed GM automatic transmissions.
- GMC truck and coach division vehicles using V, V-H and Super V transmissions
- Allison AT, MT and HT transmissions
- Sundstrand and Eaton heavy duty transmissions
- Voith transmissions
- Many hydraulic systems and rotary air compressors

**DEXRON® VI** may not meet all of the requirements of **MERCON® SP ATF** and is not licensed by Ford for this application.



# Dexron® VI ATF

## (Automatic Transmission Fluid)

### TYPICAL CHARACTERISTICS

Product	DEXRON®-VI
General Motors Qualification Number	J-60348
Product Code	
API Gravity (ASTM D-1298)	36.1
Specific Gravity (Pounds/gal)	0.844 (7.03)
Color	Red
Viscosity (ASTM D-445):	
cSt @ 40°C	28,7
cSt @ 100°C	6.0
SUS @ 100°F	152
SUS @ 210°F	46.3
Viscosity Index (ASTM D-2270)	152
Pour Point (ASTM D-97) °F (°C)	-60 (-51)
Flash Point (ASTM D-92) °F (°C)	445 (229)

**DEXRON®-VI** is a registered trademark of General Motors Corporation.

The above data is subject to usual manufacturing variation. For more information and availability, call 1-800-442-LUBE.

8/6/2008