



FORM OILS

(Concrete Release Agent)

FORM OILS are multipurpose mold release oils designed primarily for demolding concrete materials. They contain special mold release agents to aid in clean separation of concrete from various metal, wood, plastics or other types of forms. They contain no solvents.

FORM OIL 1100 is an almost colorless, light viscosity product that may be sprayed without dilution. **FORM OIL 1200** is a light colored, low-viscosity product made from slightly heavier base oil than **Form Oil 1100**.

FORM OIL 1400 is a summer grade of mold release oil, intermediate in viscosity between **FORM OILS 1300** and **1200**.

FORM OIL 1300 contains additional mold release agents and is highly viscous. It may be applied by brush or sprayed at warm temperatures.

BENEFITS:

- EXCELLENT RELEASE CHARACTERISTICS
- REDUCES CONCRETE BUILDUP ON FORMS
- NON-STAINING

TYPICAL CHARACTERISTICS

Product Code	17110	17112	17114	17113
Product Grade Name	1100	1200	1400	1500
API Gravity (ASTM D-1298)	31.1	30.4	27.8	24.5
API color	0.5	L1.0	L3.0	4
Viscosity (ASTM D-445):				
cSt @ 40°C	12.3	18	68	320
SUS @ 100°F	71	96	350	1697

The above data is subject to usual manufacturing variation. For more information and availability, call 1-800-442-LUBE.
4/3/2008