



# OGL 15R

## (Asphaltic Cutback For Open Gears)

**OGL AGMA Grade 15R** is a solvent cut back asphaltic lubricant. It is extreme pressure treated and leaves a tacky, black, highly tenacious, adhesive film after the solvent evaporates. This extremely high viscosity lubricant film provides excellent protection against wear and galling and is extremely water resistant.

The high viscosity of **OGL, AGMA 15R** provides an extremely tenacious film that provides protection against galling, pitting and wear in large open gears. Its extreme pressure additives will gradually polish and planish a pitted or spalled surface to a smooth operating surface

The solvent component is chlorine free and makes for easy application. It makes this product ideal for use in an automatic lubricating system or spray application for open gear lubrication, cam and chain lubrication or wire rope field dressing.

### BENEFITS:

- Extremely tenacious film with excellent cling ability
- Excellent protection against galling pitting and wear
- Excellent water resistance
- Dispenses easily
- Chlorine free product

## TYPICAL CHARACTERISTICS

AGMA Grade	15R
Product Code	39378
Odor	Hydrocarbon
Appearance	Black fluid
API Gravity (D 4052)	20.6
Specific Gravity @ 60 °F	1.017
Pounds/gallon	8.47
4-ball EP weld point, kg	620
Timken OK load, lbs	65 (30 kg)
Base Oil Viscosity (ASTM D-445):	
cSt @ 40°C (with solvent)	2050
cSt @ 100°C (without solvent)	1263
cSt @ 100°C (with solvent)	66
Solids content (fillers)	none
Operational temperature range	15 to 220 F

The above data is subject to usual manufacturing variation. For more information and availability, call 1-800-442-LUBE.  
10/08/04