



PF&F OILS

(Paraffinic Process & Dust-Control Oils)

PF&F OILS are highly refined, dewaxed, paraffinic mineral oils intended for non-critical general purpose lubrication such as bearings and gears operating under moderate loads and temperatures, machine tools, and electric motors. They have a high viscosity index, are light colored, and are designed for a wide variety of applications.

APPLICATIONS:

- Dilution agent for inks and petroleum
- Form release oil
- Process oil in rubber and plastic manufacturing
- General purpose lubricating oil for non-critical applications
- Flushing oil
- Dust control oil

TYPICAL CHARACTERISTICS

Product Code	17201	17200	17203	17204	17205	17206	17207
Product	700	1	3	4	5	6	7
API Gravity (ASTM D-1298)	34.8	33.2	31.5	30.4	28.6	27.3	27.9
Viscosity (ASTM D-445):							
cSt @ 40°C	10.9	21.0	60.4	100	158	184	316
cSt @ 100°C	2.75	4.2	8.0	11.1	15.1	16.6	25.0
SUS @ 100°F	65	110	313	525	831	971	1697
SUS @ 210°F	36	40	53	64	80	86	127
Viscosity Index (D-2270)	88	97	98	95	95	94	102
Specific Gravity @ 60°F	0.85	0.86	0.87	0.875	0.88	0.89	0.888
Pour Point (ASTM D-97)							
°F	0	0	0	10	15	5	5
(°C)	(-18)	(-18)	(-18)	(-12)	(-9)	(-15)	(-15)
Flash Point (ASTM D-92)							
°F	360	400	450	500	490	490	554
(°C)	(182)	(204)	(232)	(260)	(254)	(254)	(290)
Color (ASTM D-1500)	L0.5	0.5	1.0	1.0	3.0	3.0	L4.5

The above data is subject to usual manufacturing variation. For more information and availability, call 1-800-442-LUBE.
8/12/03