



POWER STEERING FLUID

POWER STEERING FLUID is designed for use in power steering systems. It meets the service requirements of most U.S. and foreign manufacturers.

POWER STEERING FLUID protects hoses and seals to maintain efficient performance of the power steering units, and helps prevent leaks and squealing. It also prevents corrosion, wear, slippage, and oxidation. It will not foam and is compatible with most factory power steering fluids.

Meet requirements of:

- Chrysler MS1872
- Chrysler MS 5931-F
- Ford M2C128-C & D
- Ford M2C-138-CJ
- Ford M2C-33-F
- GM9985010
(Saginaw power steering)

May also be used for power steering applications calling for:

- Acura 08206-9002PF or G00200
- Daimler-Chrysler MB 00989-8803
- Saab 3009800
- Subaru K0Z09A0080

TYPICAL CHARACTERISTICS

Product Code	13800
API Gravity (ASTM D-1298)	30.4
Color, Visual	Amber*
Color, ASTM D 1500	L2.5
Viscosity (ASTM D-445):	
cSt @ 40°C	37.0
cSt @ 100°C	7.1
Viscosity Index (ASTM D-2270)	156
Brookfield Viscosity, cPs @ -40°C (ASTM D2893)	33,000
Pour Point F (°C) (ASTM D-97)	-40 (-40)
Flash Point F (°C) (ASTM D-92)	385 (196)

* Formerly a blue liquid.

The above data is subject to usual manufacturing variation. For more information and availability, call 1-800-442-LUBE.

6/9/04