



# PREMIUM BRAKE FLUID (OEM Quality DOT 3 Brake Fluid)

**PREMIUM BRAKE FLUID** is a specially formulated DOT-3 fluid which has a higher viscosity than service fill DOT 3 fluids. It is recommended for all drum and disc type brake systems of automobiles and trucks. It is specially formulated with higher boiling components resulting in a fluid with a higher boiling range with a high dry boiling point which far exceeds minimum specification.

**PREMIUM DOT 3 BRAKE FLUID** will not boil off when hard braking causes extreme heat and remains equally efficient in subzero temperatures. It will not cause rubber to swell and will not corrode metal parts.

**PREMIUM BRAKE FLUID** will mix perfectly with all approved DOT 3, DOT 4 or DOT 5.1 brake fluids\*.

This product conforms to the Federal Motor Vehicle Safety Standard No. 116, DOT #3, SAE J1703 and ISO 4925 as well as various state requirements.

For use in cars, trucks or buses

Minimum wet boiling point (equilibrium reflux boiling point) is 140°C (284°F).

\*Warning: DOT 5.01 is a silicone free, glycol-based brake fluid. Do not mix our product with DOT 5 (silicone-based brake fluid).

## TYPICAL CHARACTERISTICS

Product Code	13005
Viscosity, cSt	
@ -40°C	1065
@ 40°C	7.1
@ 100°C	2.0
pH	9
Appearance	clear pale yellow liquid
Dry Reflux boiling point, °C (°F)	274 (525)
Wet Reflux boiling point, °C (°F)	156 (313)
Corrosion test (6 metals)	Pass
Effect on rubber seals	Pass
Resistance to oxidation	Pass
Water tolerance	Pass

The above data is subject to usual manufacturing variation.

For more information and availability, call 1-800-442-LUBE.

6/28/07