



RP 13

(Engine Oil With Enhanced Rust Inhibition)

RP 10 and 13 are quality engine oils formulated from high VI base stocks to provide rust protection for engines, gearboxes and hydraulic or circulating systems during shipment and storage. It is designed to displace water from metal surfaces as well as be an effective rust inhibitor. This fluid provides wear protection, detergency and dispersancy that will provide sludge and varnish protection. It also is a good general rust preventative in hydraulic and circulating oil systems in industrial applications.

RP 10 and 13 contain barium and have good protection against corrosion.

Note: If rust preventive is not be completely removed by draining, then the remaining rust preventive agent in some cases reduces key characteristics of new oil which could include foam inhibition, load carrying ability, water separation, etc.

BENEFITS:

- LONG INDOOR CORROSION PROTECTION
- IDEAL FOR STORAGE OF ENGINES, HYDRAULIC OR CIRCULATING SYSTEMS

APPLICATIONS

RP 10 and 13 are designed to protect the circulating systems of equipment that will be stored or shipped. They may also be used in systems that require better protection from rust.

They may also be used as “break-in oil” for engines.

TYPICAL SPECIFICATIONS

| | | |
|--|----------------|----------------|
| Product code | NA | 13908 |
| Grade | 10 | 13 |
| SAE Grade | 10W | 30W |
| Appearance | Amber Liquid | Dark Amber |
| Color (ASTM D-1500) | 1.5 | 4.5 |
| Specific Gravity @ 60/60 F | 0.882 | 0.89 |
| Density @ 60 °F, lbs/gal | 7.3 | 7.4 |
| Viscosity, cSt @ 40 °C | 36.5 | 91 |
| Viscosity, cSt @ 100 °C | 6.2 | 10.5 |
| Viscosity Index | 116 | 97 |
| Flash Point, COC, °F (°C) | 419 (215) | 481 (249) |
| Pour Point, °F (°C) | -27 (-33) | -10 (-24) |
| Total Base Number (D 2896) | 17 | 17 |
| Humidity cabinet, hours to fail (D 1748) | 150+ | 150+ |
| Recommended indoor storage | 6 to 12 months | 6 to 12 months |

05/04/2007