

OSYRIS 202 S

OILY FILM RUST PREVENTIVE

DESCRIPTION

OSYRIS 202 S is a premium quality petroleum based rust preventive designed to leave an oily film that prevents rust and corrosion on metal parts. This film will provide positive indoor protection from rust and corrosion for up to one year. OSYRIS 202 S is non-staining, low in odor, and can be applied by conventional brush, spray, or dip methods. Petroleum solvents or vapor degreasing easily removes this product.

TYPICAL SPECIFICATIONS

Appearance	Dark Amber Liquid
Odor	Mild Petroleum Type
Color, ASTM D-1500	3.5
Viscosity @ 40 C, cSt	14.6-16.2
Flash Point, COC, F	310
Fire Point, COC, F	330
Specific Gravity @ 60/60 F	0.868
Density @ 60 F, lbs/gal	7.23

Revised 05/03/96

TOTAL Lubricants USA, Inc.

ISO: 9001:2000 certified

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses.
We are not responsible for the misuse and/or misapplication of our products. ©2002 All rights reserved.

Linden, NJ 07036

5 North Stiles Street
908.862.9300 800.526.4127

Rockingham, NC 28379

709 Airport Road
800.323.3198

Knoxville, TN 37914

3315 Riverside Drive
800.323.3198