

OSYRIS 312 S

RUST PREVENTIVE & PENETRATING OIL

(Formerly Protera 312)

DESCRIPTION

OSYRIS 312 S is a versatile, highly penetrating rust preventive that protects tools and work-in-progress against rust and corrosion. The low viscosity nature of this product assures that crevices and pores are effectively penetrated to provide complete surface coverage. OSYRIS 312 S has excellent moisture-displacing properties, and leaves a non-gumming protective film. Protection from rust can last up to 12 months for indoor applications. OSYRIS 312 S resists oxidation and is non-staining so it can be applied safely to all metals and surfaces.

OSYRIS 312 S is also an effective degreaser and speeds disassembly of rusted and corroded parts. Additionally, it's good dielectric properties assist in preventing electrical shorts when starting-up wet motors.

TYPICAL SPECIFICATIONS

Appearance	Clear Amber Liquid
Odor	Pleasant scent
Color, ASTM D-1500	2.5
Viscosity @ 40 C, cSt	2 - 3
Flash Point, COC, F	110
Specific Gravity @ 60/60 F	0.824
Density @ 60 F, lbs/gal	6.860
Humidity Cabinet, D-1748, days	60
Salt Fog @ 5%, hours	60
Film Type	Soft Wax/ Oily film

CAUTION: COMBUSTIBLE MATERIAL

This product is not intended for high temperature applications. Do not use near heat, sparks, or open flame. Consult MSDS for further safety information.

Revised: 02/03 WHC

TOTAL Lubricants USA, Inc.

ISO: 9001:2000 certified

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses.
We are not responsible for the misuse and/or misapplication of our products. ©2002 All rights reserved.

Linden, NJ 07036

5 North Stiles Street
908.862.9300 800.526.4127

Rockingham, NC 28379

709 Airport Road
800.323.3198

Knoxville, TN 37914

3315 Riverside Drive
800.323.3198