

VALONA 2440 S

CUTTING OIL

(Formerly Elfcut 2440)

DESCRIPTION

VALONA 2440 S is a premium quality petroleum-based cutting lubricant specially designed to provide excellent metal removal, superior parts finish, and prolonged tool life in various metalworking operations on ferrous metals. VALONA 2440 S is a clear amber product fortified with high quality extreme pressure, anti-weld, and metal wetting agents.

VALONA 2440 S is not recommended for use on copper or its alloys as it will cause staining on these type metals.

TYPICAL SPECIFICATIONS

Appearance	Clear Amber Liquid
Odor	Mild Sulfur Type
Color, ASTM D-1500	1.5
Viscosity cSt @ 40°C	24 - 26
Flash Point, COC, F	320
Fire Point, COC, F	335
Specific Gravity @ 60/60 F	0.903
Density @ 60 F, lbs/gal	7.52
Copper Corrosion, ASTM D-130	4c
Chlorine, % wt.	1.0
Total Sulfur, % wt.	0.7
Active Sulfur, % wt.	0.5

Revised: 07/06/00 WCR

Replaces: 11/07/96

TOTAL Lubricants USA, Inc.

ISO: 9001:2000 certified

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses.
We are not responsible for the misuse and/or misapplication of our products. ©2002 All rights reserved.

Linden, NJ 07036

5 North Stiles Street
908.862.9300 800.526.4127

Rockingham, NC 28379

709 Airport Road
800.323.3198

Knoxville, TN 37914

3315 Riverside Drive
800.323.3198