

KSL[®] 111 – SafeGard[®] Spray

SAFEGARD 111 SYNTAC LUBE

Synthetic Spray Lubricant

KSL 111 (SafeGard 111 Syntac Lube) Synthetic Spray Grease is a light-colored compound with outstanding lubricity and anti-wear properties. It is tacky, adhesive, possesses high surface polarity and resists moisture and oxidation. It dissolves varnish deposits and protects against rust and corrosion. Use it to prolong life of equipment over a wide temperature range from 0° F to 250°F. It is packaged in convenient SafeGard cans.

Use KSL 111 (SafeGard 111 Syntac Lube) on roller, link, conveyor, and transfer chains, motorcycle chains, chain saws, cams, guides, slides, and high-speed open gears.

SafeGard Spray System

The **SafeGard Spray System** is environmentally friendly because it uses no ozone depleting agents as propellants. A bladder system and air pressure forces the lubricant out delivering a fine continuous spray that can even be sprayed upside down.

Features

- Contains synthetic diester fluid
- Excellent lubricity
- Contains anti-wear additives
- Tacky-adhesive, highly polar
- Resists moisture and oxidation
- Helps dissolve previously formed petroleum deposits

Applications

- Roller, Link, Conveyor, and Transfer Chains
- Chain Saws, Cams
- Guides
- Slides

Typical Properties

Appearance	Light Amber	Rust Test, ASTM D-1743	Pass
Texture	Smooth, Tacky	Operating Range, °F	0 – 250
Base Soap Type	Special	Base Oil:	
NLGI Grade	00	Viscosity, SUS @ 100°F	3780
		Viscosity, SUS @ 210°F	600

Revised 11/06 WHC

TOTAL Lubricants USA, Inc.

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. ©2002 All rights reserved.

Linden, NJ 07036
5 North Stiles Street
908.862.9300 800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198