

NEVASTANE[®] 6

Food Machinery Oil – SafeGard[®] Spray

Nevastane 6 is a general purpose food machinery oil, that makes it easy to save time and money with just the right amount of spray applied quickly and cleanly in the right places. Nevastane 6 is formulated from U.S.P. white oils and additives which enable it to wet out on metal surfaces better than usual white oils providing rust protection after washdown. It is resistant to acids and alkalis encountered in food processing. This surface wetting and penetration ability allows Nevastane 6 to provide superior resistance to water, steam, and mild acids. The Nevastane 6 formula contains all the right ingredients to offer superior lubrication and protection compared to other "all purpose" oils for food machinery lubrication.



NSF H-1 Registered meets USDA 1998 H-1 Guidelines for incidental contact with food.

SafeGard Spray System

The **SafeGard Spray System** is environmentally friendly because it uses no ozone depleting agents as propellants. A bladder system and air pressure forces the lubricant out delivering a fine continuous spray that can even be sprayed upside down.

Features

- NSF registered H-1 for incidental food contact
- Excellent surface wetting
- Displaces moisture, resists steam and mild acids
- SafeGard container
- Multi-purpose lubricant and penetrant
- Superior lubricity to white oils
- Colorless and odorless

Performance

- Assures government compliance
- Penetrates fast
- Protects equipment from corrosion
- Saves times and prevents spillage
- All kinds of uses
- Improved protection and extended component life
- Non-staining

Applications

- Conveyor lines
- Slides
- Guides
- Bearings
- Chains
- Sanitary Valves
- Can Making
- Rust preventative
- Widely used in textile
- Pharmaceutical plants

Industries Served

- Food and Beverage
- Pharmaceutical
- Hospital
- Bakery
- Dairy
- Textile
- Poultry Plants
- Agriculture
- Brewery
- Fruit & Vegetable

Typical Properties

NSF Registration #	127081	Flash Point, °F	420
ISO Viscosity Grade	100	Pour Point, °F	-10
SAE Viscosity Grade	30	Appearance	Water White
Rust Protection, ASTM D130	72 Hours	Film Type	Oily

Revised 10/06 WHC

TOTAL Lubricants USA, Inc.

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. ©2002 All rights reserved.

Linden, NJ 07036
5 North Stiles Street
908.862.9300 800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198