

423 Open Gear Lubricant

SafeGard® Spray

423 is an easily applied, open gear lubricant that protects gears. As all spray lubricants are cut back with solvent for ease in spraying, it is recommended that the lubricant be allowed to dry for at least thirty minutes to allow the tough film to form before putting the gears in motion.

The **SafeGard Spray System** is environmentally friendly because it uses no ozone depleting agents as propellants. A bladder system and air pressure forces the lubricant out delivering a fine continuous spray that can even be sprayed upside down.

Applications

- Open Gears
- Chains
- Sliding Surfaces
- Wire Rope
- Cables
- Flexible Couplings

Benefits

- Protects Gear Teeth
- Positive Lubrication
- Cushions Shock Loading
- Highly Adhesive; Tacky
- Reduces Wear
- Water Proofs
- Prevents Corrosion

Properties

Product Code#:

800164

Texture:

Smooth, Tacky

Appearance:

Black

Revised 10/06 WHC

TOTAL Lubricants USA, Inc.

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. ©2002 All rights reserved.

Linden, NJ 07036
5 North Stiles Street
908.862.9300 800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198