

BAR & CHAIN OIL



CHAIN SAW
LUBRICATION



Chain and chain saw oil

APPLICATIONS

- **BAR & CHAIN OIL** is a tacky lubricant made especially for chain saws.
- **BAR & CHAIN OIL** clings to the moving chain and operates from 32 F to above 100 F. It may be used on industrial roller chains, slides and other areas where clinging, anti-wear oil is required.

ADVANTAGES

- Resists sling off and splatter
- Protects against bar and chain wear
- Lengthens chain and bar life
- Rust and corrosion inhibited
- Foam inhibited

TYPICAL CHARACTERISTICS—BAR & CHAIN OIL

ISO grade	150
Specific gravity @ 60/60 °F (ASTM D 1298)	0.922
Viscosity at 40°C, cSt (ASTM D 445)	150
Color (ASTM D 1500)	4.0
Flash point, COC, °F (ASTM D 92)	400 (204)
Pour point, °F/°C (ASTM D 97)	+15 (-9)

TOTAL Lubricants USA Southwest

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418
Plano, Texas 75075
800-442-5823 or 469-241-0950
www.finalube.com

Bar & Chain Oil
Sheet updated: 9/2009

5 North Stiles Street
Linden, New Jersey 07036
800-526-4127 or 908-862-9300
www.total-us.com