

BRICK OIL



NON-CRITICAL
LUBRICATION



Light duty chain and cutting oil

APPLICATIONS

Non-critical lubrication

- **BRICK OIL** is low viscosity mineral oil intended for non-critical general purpose lubrication such as bearings and gears operating under moderate loads and temperatures, machine tools and electric motors. It is also suitable as a dust control oil or flushing oil.
- **BRICK OIL** may vary from batch to batch in color, density and viscosity.

ADVANTAGES

- Good penetration
- Good lubricity
- Light color
- Economical

TYPICAL CHARACTERISTICS—BRICK OIL

ISO Grade	22
Specific gravity @ 60/60°F ASTM D 1298	0.86
Viscosity at 40°C, cSt ASTM D 445	18
Viscosity at 100°C, cSt ASTM D 445	3.8
Color, ASTM D 1500	2.5

* Density and viscosity at 100 degrees Centigrade will vary from batch to batch.

TOTAL Lubricants USA Southwest

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418
Plano, Texas 75075
800-442-5823 or 469-241-0950
www.finalube.com

Brick Oil
Sheet updated: 9/2009

5 North Stiles Street
Linden, New Jersey 07036
800-526-4127 or 908-862-9300
www.total-us.com