


CLASSIC SM-GF4 OILS



SAE 5W-20, 5W-30 & 10W-30



Passenger car motor oil with API SM/GF-4 credentials

APPLICATIONS

All types of service

- **CLASSIC SM-GF4** multi-grade oils are designed to meet lubrication requirements of today's naturally aspirated, turbo-charged and super-charged gasoline fueled engines.
- **CLASSIC SM-GF4** multi-grade oils are formulated to provide excellent oxidation stability, low temperature flow properties and enhanced fuel economy. They also meet the low volatility requirements of ILSAC GF-4 for improved engine cleanliness and reduced oil consumption.

PERFORMANCE

API SM
ILSAC GF-4

CUSTOMER BENEFITS

Increased drain intervals

High technical performance

- Its higher performance level allows longer drains intervals with fuel economy. Most US car manufacturers recommend 5,000 to 7,000 mile drain intervals in these fuel economy multi-grade oils.
- Enhanced detergents, dispersants, anti-oxidants, anti-wear and corrosion prevention properties improve the fluid performance under all types of service.
- Excellent low temperature flow properties ensuring easy cold starts. Engine components are lubricated quickly giving longer life.

CHARACTERISTICS

PROPERTY	5W-20	5W-30	10W-30
Specific gravity @ 60/60°F	0.865	0.864	0.867
Viscosity, cSt @ 100°C (ASTM D 445)	8.1	10.65	10.50
Viscosity, cSt @ 40°C (ASTM D 445)	49	66	62
Viscosity Index (ASTM D 2270)	140+	150+	150+
Cold crank simulator, cp @ (ASTM D 5293)	5500@ -30°C	6000@ -30°C	6100@ -25°C
Pour Point, °F (°C) (ASTM D 97)	-33 (-36)	-33 (-36)	-22 (-30)
NOACK, (15 wt% max loss)	Pass	Pass	Pass

TOTAL Lubricants USA Southwest

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418
Plano, Texas 75075
800-442-5823 or 469-241-0950
www.finalube.com

Classic SM-GF4 Oils
Sheet updated: 05/2009
Label reference: --

5 North Stiles Street
Linden, New Jersey 07036
800-526-4127 or 908-862-9300
www.total-us.com