

CALPLEX WR



GREASE



TOTAL

Multi-purpose, calcium sulfonate grease

APPLICATIONS

Adhesive,
multi-purpose,
extreme pressure
industrial & automotive
grease

- **CALPLEX WR GREASE** is an NLGI 2 grade, heavy-duty grease designed for a wide range (WR) of applications. It is compounded from selected base oils and a calcium sulfonate thickener. It is non-staining towards yellow metals at elevated temperatures (250+F) unlike most multi-purpose lithium greases.
- **CALPLEX WR GREASE** is highly water-resistant, corrosion-resistant grease with excellent EP properties. It is highly recommended for marine, industrial, automotive, agricultural and construction equipment. It is an excellent chassis and wheel bearing grease for both on and off-road equipment and an excellent multi-purpose industrial grease.

SPECIFICATIONS

- ISO 6743-9: L-XCGGB-2
- DIN 51502: KP2P-20

ADVANTAGES

Long life durable grease
excellent corrosion
resistance

- Miscible with the majority of other conventional soap greases.
- Durable and resistant to water, pollution, and temperature variations.
- Good adhesion to metals.
- Excellent corrosion resistance including salt fog and sea water
- Excellent EP at both high and low temperatures due to special thickener
- Good mechanical and thermal stability under stress and high temperature
- Extends service intervals

TYPICAL CHARACTERISTICS CALPLEX WR GREASE	
Appearance, visual	Smooth tan grease
Thickener type	Calcium sulfonate
NLGI grade	2
Penetration worked 60x, ASTM D 217	280
Dropping point, °F (°C) ASTM D 2265	570 (288)
4 Ball weld load, kg. ASTM D 2596	500
Load wear index	65
Timken OK load, lbs ASTM D-2509	70
Base oil viscosity @ 40°C, cSt ASTM D 445	120
Operating range, °F	0 - 325

TOTAL Lubricants USA Southwest

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418,
Plano, Texas 75075
800-442-5823 or 469-241-0950
www.finalube.com

Calplex WR Grease
Sheet updated: 9/2009

5 North Stiles Street
Linden, NJ 07036
908.862.9300 or 800.526.4127
www.total-us.com