

# DRIP OIL

## WATER PUMP LUBRICANT



Non-potable water well, turbine pump lubricant

### APPLICATIONS

- **DRIP OIL** is a light bodied mineral oil containing no additives. It is for lubrication of vertical deep water well turbine pump bearings.

### SPECIFICATIONS

None

### ADVANTAGES

**Economical lubricant**

- Excellent low temperature fluidity
- Inherent lubricity minimizes wear
- Economical lubricant

TYPICAL CHARACTERISTICS—DRIP OIL	
Specific gravity at 60 F (ASTM D 1298)	0.858
API gravity at 60 F (ASTM D 1298)	33.3
Density, lbs./gal (ASTM D 1298)	7.15
Viscosity @ 40°C, cSt (ASTM D 445)	21.9
Viscosity @ 100°C, cSt (ASTM D 445)	4.27
Viscosity Index (ASTM D 2272)	95
Pour point, °F (°C) (ASTM D 97)	-17 (-27)
Flash point °F (°C) (ASTM D 92)	330 (165)

TOTAL Lubricants USA Southwest

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418,  
Plano, Texas 75075  
800-442-5823 or 469-241-0950  
www.finalube.com

**Drip Oil**  
Sheet updated: 9/2009

5 North Stiles Street  
Linden, NJ 07036  
908.862.9300 or 800.526.4127  
www.total-us.com

TOTAL Lubricants USA with a policy of continuous improvement, reserves the right to change specifications as our technology progresses.  
We are not responsible for the misuse and/or misapplication of our products. MSDS are found on our web sites.