

FLUID MULTI CVT



TOTAL

Super premium synthetic multi-vehicle ATF

APPLICATIONS

Types of service

- **FLUID MULTI CVT** is a super-premium quality, synthetic automatic transmission fluid. It is suitable for use in a wide array of automatic transmissions and meet the requirements of most cars and SUV's sold by US and foreign OEM's.
- **FLUID MULTI CVT** contains synthetic base stocks and unusual additives. Unlike other automatic transmission fluids, it is designed for use in continuous variable transmissions (CVTs), 5 speed and 6 speed automatic transmissions as well as conventional automatic transmissions.
- Always consult your owner's manual for its suitability as ATF in imported vehicles.

PERFORMANCE

Suitability for use

SUITABLE FOR MULTIPLE VEHICLES (Domestic and Foreign)
See page 2 for guidelines and suitability for use listings.

CUSTOMER BENEFITS

Technical benefits assure trouble-free transmission life

- Exceptional cleanliness of delicate control valves resulting in trouble-free transmission performance.
- Proper frictional properties provide the required shift feel characteristics for multiple-speed transmissions including those with CVT systems.
- Excellent anti-wear, anti-corrosion, anti-foam, oxidation resistance, stable friction modifiers, and a very shear stable VI improver assure long service life.
- Excellent low temperature fluidity protects against wear under extremely cold operating conditions.

CHARACTERISTICS

TYPICAL CHARACTERISTICS FLUID MULTI CVT	
Color, visual	Red
API gravity (lbs/gal) (ASTM D-1298)	34.9 (7.08 lbs/gal)
Brookfield viscosity cps @ -40°C (ASTM D-2893)	13,000 max
Viscosity cSt @ 40°C (ASTM D-445)	29
Viscosity, cSt @ 100°C (ASTM D-445)	6.5
Viscosity index (ASTM D-2270)	180
Pour point °F (°C) (ASTM D-97)	-46 (-51)
Flash point °F (°C) (ASTM D-92)	374 (190)

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418
Plano TX 75075
800-442-5823 or 469-241-0950
www.total-us.com

Fluid Multi CVT
Sheet Updated 5/2010

5 North Stiles Street
Linden, NJ 07036
908-862-9300 or 800-526-4127
www.total-us.com

TOTAL Lubricants USA has a policy of continuous improvement and reserves the right to change specifications as our technology progresses.
We are not responsible for the misuse and/or misapplication of our products. MSDS are found on our web sites.