

GRAPHITE POWDER



LUBRICATION



Natural graphite in powdered form

APPLICATIONS

Blending component

- Natural graphite powder is an economical grade of graphite, suitable for a variety of industrial uses as a blending component.
- **GRAPHITE POWDER** may be used as a general-purpose solid lubricant or as a blending component for plastics, etc.
- **WARNING:** Dusts from powders can be a breathing health hazard. Please consult MSDS for protective gear.

ADVANTAGES

- Good lubricity over a wide temperature range. Graphite will lubricate at very high temperatures (over 1000 F) or low temperatures.

TYPICAL CHARACTERISTICS GRAPHITE POWDER

Texture, appearance	Powder
Color, visual	Grey to black
Specific gravity	2.20-2.35
Graphite, wt % carbon	85-98
Silica, wt %	2-15

TOTAL Lubricants USA Southwest

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418
Plano, Texas 75075
800-442-5823 or 469-241-0950
www.finalube.com

Graphite Powder
Sheet updated: 9/2009

5 North Stiles Street
Linden, New Jersey 07036
800-526-4127 or 908-862-9300
www.total-us.com

TOTAL Lubricants USA has a policy of continuous improvement and reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. MSDS are found on our web sites.