

LACTUCA LT 3000-S



METALWORKING
LUBRICATION



Chlorine-free macro-emulsion for machining copper alloys and mild steels

APPLICATIONS

Soluble oil for mild
steels and copper alloys

Rust preventive

- **LACTUCA LT 3000-S** is a macro-emulsion specifically designed for the conventional machining of copper alloys and screw cutting brasses. It is also fully satisfactory for all processes involving fine carbon steels. Recommended proportions: 3 to 6 %.
- Temporary protection of mechanical parts, machined or not, where easy removal of the rust preventive is required.

SPECIFICATION

ISO 6743/7 Category L MAA

ADVANTAGES

Very easy to use

- Very easy to use: simply pour **LACTUCA LT 3000-S** into good quality water.
- Forms stable emulsion
- Good corrosion resistance of machined parts
- Excellent anti-foaming properties.
- Non-staining

CHARACTERISTICS

TYPICAL CHARACTERISTICS LACTUCA LT 3000-S	
Color ASTM D 1500	5.0
Viscosity at 40 °C, cSt ASTM D 445	41.6
Specific gravity @ 60/60°F ASTM D 1298	0.874
Flash point, COC, °F (°C) ASTM D 92	360 (182)
Emulsion stability, 24 hr modified ASTM D 3707	
A. 5% oil in distilled water	Slight ring - no oil
B. 5% oil in 340 ppm CaCO ₃	1 ml Cream cuff - no oil
Sulfur content, weight percent,	0.35
Pour point, °F (°C) ASTM D-97	+10 (-12)

HANDLING OPERATIONS-HEALTH & SAFETY

LACTUCA LT 3000-S contains no chlorine, nitrites or PTBB, NPE, DEA. **LACTUCA LT 3000-S** is produced from virgin, solvent-refined base oil, and has no particular smell.

TOTAL Lubricants USA Southwest

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418,
Plano, Texas 75075
800-442-5823 or 469-241-0950
www.finalube.com

Lactuca LT 3000-S
Sheet updated: 9/2009

5 North Stiles Street
Linden, NJ 07036
908.862.9300 or 800.526.4127
www.total-us.com

TOTAL Lubricants USA with a policy of continuous improvement, reserves the right to change specifications as our technology progresses.
We are not responsible for the misuse and/or misapplication of our products. MSDS are found on our web sites.