

# SafeGard® Moly 23 Chain Lube

SafeGard Moly 23 is an excellent high and low temperature lubricant containing a combination of colloidal molybdenum disulfide and colloidal graphite. Excellent wetting and dispersing properties carry the solid lubrications into areas with very close tolerances. SafeGard Moly 23 has a wide operating range from -20° to +600°F.

## SafeGard Spray System

The **SafeGard Spray System** is environmentally friendly because it uses no ozone depleting agents as propellants. A bladder system and air pressure forces the lubricant out delivering a fine continuous spray that can even be sprayed upside down.

### Features

- Provides positive boundary lubrication
- Wide operating temperature range
- Excellent wetting and dispersing properties
- Penetrates links
- Leaves lubricating film
- Resists "Throw-Off"
- Prevents gummy deposits

### Applications

- Bakery Ovens
- Slides
- Guides
- Ways
- Cams
- Sprockets
- Hinges

## Typical Properties

<b>Product Code #</b>	<b>200517</b>	Flash Point, °F, C.O.C. ASTM D92	310
Gravity API @ 60°F, ASTM D287	32.6	Pour Point, °F, ASTM D97	-20
Base Oil Viscosity		ASTM Viscosity Grade No.	S465
SUS @ 100°F	550	SAE No.	30
SUS @ 210°F	65	Color	Black
Viscosity Index	96		

Revised 11/06 WHC

## TOTAL Lubricants USA, Inc.

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. ©2002 All rights reserved.

Linden, NJ 07036  
5 North Stiles Street  
908.862.9300 800.526.4127

Rockingham, NC 28379  
709 Airport Road  
800.323.3198

Knoxville, TN 37914  
3315 Riverside Drive  
800.323.3198