

# NATERIA CATCO NA



**NATURAL GAS  
ENGINE OIL**



**Low-ash natural gas engine oils**

**TOTAL**

## APPLICATIONS

### Moderate service

- Lubrication of natural gas engines used where the manufacturer requires an ash level of 0.4 to 0.5 weight percent.
- Recommended for both 2-cycle and 4-cycle natural gas and LPG fueled engines working under moderate operating conditions where economy oil can be used.

## ADVANTAGES

### Technical characteristics

- **NATERIA CATCO NA** is a low-ash oil and is catalyst compatible
- Good detergency and dispersancy.
- Good chemical stability with resistance to oxidation and nitration.
- Excellent anti-wear, anti-corrosion and anti-foam resistance.

TYPICAL CHARACTERISTICS--NATERIA CATCO NA		
SAE Grade	30	40
Specific gravity @ 60/60°F (ASTM D 1298)	0.879	0.881
Viscosity @ 40°C, cSt (ASTM D 445)	86.1	127
Viscosity @ 100°C, cSt (ASTM D 445)	10.3	13.4
Viscosity Index (ASTM D 2272)	96	97
Pour point, °F (°C) (ASTM D 97)	-11 (-24)	0 (-18)
Flash point °F (°C) (ASTM D 92)	450 (232)	450 (232)
TBN (ASTM D 2896)	4.8	4.8
Sulfated Ash, wt% (ASTM D 874)	0.40	0.40

TOTAL Lubricants USA Southwest

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418,  
Plano, Texas 75075  
800-442-5823 or 469-241-0950  
www.finalube.com

5 North Stiles Street  
Linden, NJ 07036  
908.862.9300 or 800.526.4127  
www.total-us.com

TOTAL Lubricants USA with a policy of continuous improvement, reserves the right to change specifications as our technology progresses.  
We are not responsible for the misuse and/or misapplication of our products. MSDS are found on our web sites.

TOTAL Lubricants USA Southwest

TOTAL Lubricants USA, Inc.