

# Nevastane<sup>®</sup> 5P7

## Food Machinery Bearing and Open Gear Lubricant

**Nevastane 5P7 Bearing and Open Gear Lubricant** is a very tacky lube that forms a tenacious film providing load and wear protection along with superior corrosion resistance from salt and food acids. It offers excellent moisture resistance. Nevastane food machinery lubricants assure long machine life while reducing contamination problems as required by the Hazard Analysis and Critical Control Point System (HACCP).



NSF H-1 Registered meets USDA 1998 H-1 Guidelines for incidental contact with food.

Applications	Benefits
<ul style="list-style-type: none"> <li>• Open Gears</li> <li>• Valves</li> <li>• Low speed plain and anti-friction bearings</li> <li>• Cams</li> <li>• Slides</li> </ul>	<ul style="list-style-type: none"> <li>• Repels moisture</li> <li>• Tacky, adhesive grease</li> <li>• Protects against corrosion</li> <li>• Resists throw-off</li> <li>• Clear film won't stain</li> </ul>

Typical Properties	
<b>NSF Registration #</b>	<b>123543</b>
NLGI Grade:	2
Density, lb/gal @60 °F (kg/m <sup>3</sup> , 15°C):	7.55 (904)
Penetration, Worked 60 Strokes , ASTM D 217:	265 - 295
Dropping Point (ASTM D2265) °C (°F):	200 (392)
Operating Range, °F:	0 - 260
Texture:	Smooth, Tacky
Appearance:	Translucent
Thickener:	Aluminum Complex
<b>Base Oil Properties:</b>	
Viscosity: Centistokes @ 40 °C	967
Viscosity: Centistokes @ 100 °C	53.0
Viscosity Index	103
Flash Point, ASTM D 92, °C (°F):	230 (446)
Pour Point, ASTM D 97, °C (°F):	-15 (5)

Revised 10/06 WHC

### TOTAL Lubricants USA, Inc.

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. ©2002 All rights reserved.

Linden, NJ 07036  
5 North Stiles Street  
908.862.9300 800.526.4127

Rockingham, NC 28379  
709 Airport Road  
800.323.3198

Knoxville, TN 37914  
3315 Riverside Drive  
800.323.3198