

Nevastane[®] 5

Semi-Fluid Food Machinery Lubricant

Nevastane 5 is a semi-fluid lubricant that finds application in the food processing plant where a light but non-drip film of lubricant is needed. It helps to assure long machine life while reducing contamination problems as required by the Hazard Analysis and Critical Control Point System (HACCP).



NSF H-1 Registered meets USDA 1998 H-1 Guidelines for incidental contact with food.

Applications	Benefits
<ul style="list-style-type: none"> • Can covers in stack • Slides • Guides • Chains • Plain and Anti-friction bearings • Light duty gear reducers 	<ul style="list-style-type: none"> • Non-toxic • No taste or odor • Pumps easily • Non-dripping

Typical Properties	
NSF Registration #	123542
Appearance	Translucent
Film type	Oily
Consistency	Semi-Fluid
Brookfield Viscosity @ 77°F, cps, #4 Spindle, 12 rpm	6500 - 8500
Base Oil Properties:	
Viscosity, 40 °C cSt,	68.3
Flash Point, C.O.C., °C (°F)	224 (435)
Pour Point, °C (°F)	-12 (+10)

Revised 10/06 WHC

TOTAL Lubricants USA, Inc.

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. ©2002 All rights reserved.

Linden, NJ 07036
5 North Stiles Street
908.862.9300 800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198