

Penetrating Oil 2

Light Lubricant & Cleaner

A high quality penetrating lubricant, and gum/ varnish solvent. Recommended for cleaning hydraulic systems and flushing speed reducers and bearings.

Hydraulic Systems: Add 5% by volume circulate for 24 to 100 hours. Drain and refill.

Enclosed Gears: Add 10% by volume, operate for 24 to 48 hours. Drain and refill.

Bearings: Use as a flush to eliminate old lubricant residue build-up.

Applications

- Cleaning agent to remove gums and sludge from bearings, gears, etc.
- Light machinery lubricant for sewing machines, office and household equipment
- Fishing reels
- Cleaning and polishing guns (prevents rust)
- Chains
- Small Bearings

Method of Application

- Oil Can
- Oil Cups
- Brush Type Oilers

Typical Properties

Product Code #	200136	Pour Point, ASTM D 97, °F	-5
Viscosity, SUS @ 100°F	55	Gravity ASTM D 287 API	35.2
Flash Point, ASTM D 92, °F	100 min.	Ash, %	None

JAC 07/2006

TOTAL Lubricants USA, Inc.

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. ©2002 All rights reserved.

Linden, NJ 07036
5 North Stiles Street
908.862.9300 800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198