

# POWER STEERING FLUID BASE



LUBRICATION



High viscosity index base oil

## APPLICATIONS

Compounder Blender

- **POWER STEERING FLUID BASE** is designed for use for compounders and blenders as a base fluid for power steering fluid. When properly additized it will meet the service requirements of most power steering units for operation over a wide temperature range

## ADVANTAGES

Characteristics

- High viscosity index with excellent shear stability.
- Foam inhibited
- Very low pour point

### TYPICAL PROPERTIES—POWER STEERING FLUID BASE

Specific Gravity @ 60/60°F	ASTM D 1298	0.862
Color	ASTM D 1500	0.5
Viscosity at 40°C, cSt	ASTM D 445	33.2
Viscosity at 100°C, cSt	ASTM D 445	5.87
Viscosity Index	ASTM D 2270	120
Flash Point, COC, °F (°C)	ASTM D 92	404 (207)
Pour Point, °F (°C)	ASTM D 97	--44 (-42)

TOTAL Lubricants USA Southwest

400 Chisholm Place, Suite 418  
Plano, Texas 75075  
800-442-5823 or 469-241-0950  
[www.finalube.com](http://www.finalube.com)

Power Steering Fluid Base  
Sheet updated 8/2009

TOTAL Lubricants USA, Inc.

5 North Stiles Street  
Linden, New Jersey 07036  
800-526-4127 or 908-862-9300  
[www.total-us.com](http://www.total-us.com)