

PURE MINERAL GEAR OIL



NON-CRITICAL
LUBRICATION



API GL-1 (non-additized) gear oil

APPLICATIONS

- **PURE MINERAL GEAR OILS** are economical lubricant containing no additives.
- **PURE MINERAL GEAR OILS** satisfy API Service GL-1 specifications. They are primarily used in truck manual transmissions. In some cases they may be recommended for automotive worm gears or as dedusting oils.

ADVANTAGES

- Good lubricity and low odor
- Good low temperature flow properties
- Low odor

TYPICAL CHARACTERISTICS—PURE MINERAL GEAR OIL

SAE grade	90	140
Specific gravity @ 60/60 °F (ASTM D 1298)	0.887	0.891
Viscosity at 40°C, cSt (ASTM D 445)	226	480
Viscosity at 100°C, cSt (ASTM D 445)	19	32
Viscosity index (D 2272)	94	97
Pour point, COC, °F (°C) (ASTM D 97)	0 (-18)	5 (-15)
Color, (ASTM D 1500)	6.0	6.5

TOTAL Lubricants USA Southwest

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418
Plano, Texas 75075
800-442-5823 or 469-241-0950
www.finalube.com

Pure Mineral Gear Oil
Sheet updated: 9/2009

5 North Stiles Street
Linden, New Jersey 07036
800-526-4127 or 908-862-9300
www.total-us.com

TOTAL Lubricants USA has a policy of continuous improvement and reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. MSDS are found on our web sites.