

SHAKE/SHINGLE OIL



WOOD DRESSING



Oil dressing for wood roofs

APPLICATIONS

Wood dressing for fences and roofs

- **SHAKE/SHINGLE OIL** is highly refined oil, which may be used to treat wooden structures. This wood dressing extends the useful life of the wood. This oil is light in color and has good penetrating ability. It contains no biocide, pigments or preservatives or environmentally harmful ingredients.
- **SHAKE/SHINGLE OIL** should be applied to new shake or shingle roofs or to older roofs that have been pressure washed to remove dirt, leaves, etc. This oil penetrates and is non-drying. It may be used on roofs, fences and other wood structures. Oil should be applied sparingly since it is absorbed into the wood. It may be applied by moping, spraying or brushing.

ADVANTAGES

- Low viscosity penetrates into wood
- Bright and clear with low color
- Non-staining
- Extends useful life of wooden structure

TYPICAL CHARACTERISTICS—SHAKE/SHINGLE OIL

Color, visual	Yellow to Light Amber
Specific Gravity @ 60/60°F (ASTM D 1298)	0.910
Flash Point, COC, °F (°C) (ASTM D 92)	325 (163)

TOTAL Lubricants USA Southwest

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418
Plano, Texas 75075
800-442-5823 or 469-241-0950
www.finalube.com

Shake/Shingle Oil
Sheet updated: 9/2009

5 North Stiles Street
Linden, New Jersey 07036
800-526-4127 or 908-862-9300
www.total-us.com