


XENOR GREASE



GREASE



Stiff multi-service lithium complex grease

APPLICATIONS

**Agricultural
and industrial uses**

- **XENOR GREASE** is high performance extreme pressure grease compounded with extreme pressure (EP) and anti-wear additives, which, coupled with the high viscosity base oils, produce a high load carrying ability and reduce wear.
- **XENOR GREASE** is recommended for a multitude of applications including heavy-duty vehicles and equipment used in construction, mining, and agriculture, logging and hauling. It is also ideal for many industrial applications in paper mills, cement plants, metalworking shops, power plants, chemical manufacturing facilities, textile mills, plastics plants, food processors, sawmills, foundries, wastewater treatment plants and steel mills.

SPECIFICATIONS

ISO 6743-9: L-XBEHB 3
DIN 51502: KP3P-10

ADVANTAGES

**Good lubricant film and
wash resistance**

- Reduced wear and good EP properties
- Anti-oxidation and anti-corrosion/anti-rust properties.
- Good water resistance

TYPICAL CHARACTERISTICS XENOR GREASE #3	
NLGI Grade	3
Appearance,	Smooth, tan grease
Thickener Type,	Lithium Complex
Penetration Worked, 60x (ASTM D 217)	240
Dropping Point, °F (°C) (ASTM D 2265)	530 (278)
Timken OK Load, lbs (ASTM D-2509)	50
Four Ball EP Weld Point, kg (ASTM D-2596)	250
Load Wear Index, kg	45
Base oil viscosity @ 40°C, cSt (ASTM D 445)	150
Operating Range, °F	+10 to 325

TOTAL Lubricants USA Southwest

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418,
Plano, Texas 75075
800-442-5823 or 469-241-0950
www.finalube.com

Xenor Grease #3
Sheet updated: 9/2009

5 North Stiles Street
Linden, NJ 07036
908.862.9300 or 800.526.4127
www.total-us.com