

SILICONE

Release Agent and Lubricant – SafeGard® Spray

Silicone - Release Agent & Lubricant provides safe lubrication with very thin films. Silicone, with its high flash point is resistant to heat and oxidation. It lubricates and protects from -40°F to +400°F without freezing or gumming. Silicone is odorless, non-toxic, greaseless, and non-staining. This product is NSF H-1 registered and meets USDA 1998 H-1 Guidelines for incidental contact with food.



NSF H-1 Registered meets USDA 1998 H-1 Guidelines for incidental contact with food.

SafeGard Spray System

The **SafeGard Spray System** is environmentally friendly because it uses no ozone depleting agents as propellants. A bladder system and air pressure forces the lubricant out delivering a fine continuous spray that can even be sprayed upside down.

Features

- Wide temperature range
- Insulates
- Lubricates
- Stops squeaking
- Odorless
- Colorless
- Does not stain

Applications

- Mold release agent – plastic and rubber
- Timers, TV tuners, Clocks, Electrical equipment
- Bushings
- Bearings
- Chains
- Camera Gears
- Motion Picture equipment
- Automotive – battery terminals, rubber, gasket, etc.
- Printing and Textile Industries – Cutters, punches, forms, saws, knives, tables, presses
- Food Industry – packaging equipment lubricant

Typical Properties

| | |
|---------------------|--------------------------------|
| Film Color | Transparent |
| Consistency of Film | Slippery |
| Surface Drying | Dries to Thin Lubricating Film |

Revised 10/06 WHC

TOTAL Lubricants USA, Inc.

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. ©2002 All rights reserved.

Linden, NJ 07036
5 North Stiles Street
908.862.9300 800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198