

Wire Rope Dressing 00

Solvent Cutback Asphaltic Lubricant

Wire Rope Dressing 00 is a special lubricant for wire rope that penetrates into the strands when applied properly but dries to a tough durable coating outside that provides excellent protection against wear and galling. The highly tenacious, adhesive film offers excellent lubrication as well as corrosion protection.

Applications	Features
<ul style="list-style-type: none"> • In-service or field dressing wire rope lubrication • “Lay-up” wire rope lubrication <p>Methods of Application: Spray, Wipe, Drip, Brush, Pressure applicator, Automatic Lubrication System</p>	<ul style="list-style-type: none"> • Extreme pressure wear protection • Very adhesive film (water repellent) • Penetrates wire strands • Displaces moisture • Prevents rust • Acidic and alkaline environment resistant <ul style="list-style-type: none"> • Dispenses easily • No lead or trichloroethane

Properties	
Base Oil Viscosity, Kinematic, cSt at 40°C	125
Base Oil Viscosity, Saybolt at 100°F	580
Flash Point, C.O.C., °F (without solvent):	370
Flash Point, C.O.C., °F (with solvent):	129
Pour Point, °F:	-10
Density, lb./gal, 60°F:	7.96
Appearance:	Black Fluid

Revised 10/06 WHC

TOTAL Lubricants USA, Inc.

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. ©2002 All rights reserved.

Linden, NJ 07036
5 North Stiles Street
908.862.9300 800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198